PUBLIC VERSION

UNITED STATES INTERNATIONAL TRADE COMMISSION
Washington, D.C.

Before The Honorable David P. Shaw
Administrative Law Judge

In the Matter of

CERTAIN ELECTRIC FIREPLACES, COMPONENTS THEREOF, MANUALS FOR SAME, CERTAIN PROCESSES FOR MANUFACTURING OR RELATING TO SAME AND CERTAIN PRODUCTS CONTAINING SAME

Inv. No. 337-TA-791/826

JOINT MOTION TO TERMINATE INVESTIGATION AS TO RESPONDENT WHALEN FURNITURE MANUFACTURING, INC. BASED ON SETTLEMENT AGREEMENT, CONSENT ORDER STIPULATION AND PROPOSED CONSENT ORDER AND TO STAY OF THE PROCEDURAL SCHEDULE AS IT RELATES TO WHALEN FURNITURE MANUFACTURING, INC.

Complainants Twin-Star International, Inc. and TS Investment Holding Corporation (collectively, "Twin-Star" or "Complainants") and Respondent Whalen Furniture Manufacturing, Inc. ("Whalen") hereby jointly move for termination of this investigation as to Whalen pursuant to § 210.21 and for a stay of the procedural schedule as it relates to Whalen. Entry of the Consent Order will resolve this investigation with respect to Whalen rendering termination with respect to Whalen appropriate.[1] Additionally, in view of the upcoming Procedural Schedule deadlines, a stay is appropriate so that the private parties, Commission Investigative Staff ("Staff") and Commission do not have to expend time, effort and resources that are unnecessary in view of the relief sought in this motion.

Staff has indicated that it will file a response.

[1] As indicated below, Complainants are withdrawing certain allegations in the 826 Complaint, and Complainants and Whalen have entered into a settlement agreement.

I. TERMINATION OF THIS INVESTIGATION AS TO WHALEN IS APPROPRIATE BASED ON THE SETTLEMENT AGREEMENT AND PROPOSED CONSENT ORDER

A Consent Order Stipulation executed by Whalen is attached as Exhibit 1. A proposed Consent Order is attached as Exhibit 2. A copy of the Parties' Settlement Agreement is attached as Exhibit 3. There are no agreements, written or oral, express or implied, between Complainants and Whalen concerning the subject matter of this Investigation other than the Confidential versions of those submitted herewith.

The United States International Trade Commission ("Commission") instituted the above-captioned investigation (the "Investigation") under Section 337 of the Tariff Act of 1930 as amended (19 U.S.C. § 1337), based upon the allegations in the Complaint filed by Twin-Star, which alleged unfair acts in the importation into the United States, the sale for importation, and the sale within the United States after importation, of certain electric fireplaces, components thereof, manuals for same, certain processes for manufacturing or relating to same and certain products containing same ("Subject Electric Fireplaces") by, among others, Respondent Whalen Furniture Manufacturing Inc. ("Whalen").

Twin-Star and Whalen jointly request entry of the proposed Consent Order attached at Exhibit 2, based on the stipulation attached at Exhibit 1 and the Settlement Agreement attached at Exhibit 3 to this joint motion. Termination of the investigation based on the terms of the Settlement Agreement and entry of the proposed Consent Order will render moot the dispute with respect to Twin-Star's allegations of trade secret misappropriation and copyright infringement against Whalen in the 826 Investigation. Twin-Star hereby withdraws its allegations before the Commission of tortious interference with contract against Whalen.

Accordingly, the Settlement Agreement and proposed Consent Order resolve all claims against Whalen before the Commission.

Granting this motion for termination of this investigation as to Whalen is in the public interest, which favors the settlement of disputes to avoid needless litigation and to conserve resources. *See, e.g.*, *Certain Compact Disc and DVD Holders,* Inv. No. 337-TA-482, Order No. 11 at 3 (March 7, 2003). Granting this motion for termination of this investigation as to Whalen will streamline the case for hearing by removing one of the respondents and will result in savings of Commission and party resources. Entry of the proposed Stipulation and Consent Order will not impose an undue burden on the public health and welfare, competitive conditions in the United States economy, production of like or directly competitive articles in the United States, or United States consumers.

II. A STAY OF THE PROCEDURAL SCHEDULE AS IT RELATES TO WHALEN IS APPROPRIATE

A stay of the procedural schedule as it relates to Whalen is appropriate in view of the relief being sought by this motion. There are several upcoming deadlines as set forth in the Procedural Schedule. However, the requested entry of the Consent Order will resolve this investigation as to Whalen. There is no need for the private parties, staff and the Commission to expend additional time, effort and resources on the investigation as it relates only to Whalen.[2]

III. CONCLUSION

Accordingly, Twin-Star and Whalen respectively request that the Administrative Law Judge issue an Initial Determination that the Investigation be terminated as to Whalen and that

[2] After entry of the proposed Consent Order and termination of this Investigation as to Whalen, the only remaining respondents will be Reliap and Yue Qiu Sheng (aka Jason Yue), neither of whom have participated in this Investigation since their counsel, Kenyon & Kenyon, entered a Notice of Withdrawal on March 12, 2012.

the proposed Consent Order be entered. In addition, Twin-Star and Whalen respectively request that the Administrative Law Judge stay the proceedings as to Whalen during the pendency of this joint motion to terminate.

Respectfully submitted,

Dated: May 11, 2012

/s/ Jeffrey J. Catalano
Michael P. Chu
Robert S. Mallin
BRINKS HOFER GILSON & LIONE
NBC Tower, Suite 3600
455 North Cityfront Plaza Drive
Chicago, IL 60611-5599
(312) 321-4200 (phone)
(312) 321-4299 (fax)

Jay H. Reiziss
BRINKS HOFER GILSON & LIONE
1850 K Street N.W.
Washington, D.C. 20006
(202) 296-6941 (phone)
(202) 296-8701 (fax)

Attorneys For Twin-Star International Incorporated and TS Investment Holding Corp.

Dated: May 11, 2012

/s/ Randall S. Waier
Randall S. Waier
Law Offices of Randall S. Waier
20241 Birch Street, Suite 103
Newport Beach, CA 92660
(949) 476-2511 (phone)
(949) 476-3160 (fax)

Attorney For Whalen Furniture Manufacturing, Inc.

EXHIBIT 1

UNITED STATES INTERNATIONAL TRADE COMMISSION
Washington, D.C.

Before The Honorable David P. Shaw
Administrative Law Judge

In the Matter of

CERTAIN ELECTRIC FIREPLACES, COMPONENTS THEREOF, MANUALS FOR SAME, CERTAIN PROCESSES FOR MANUFACTURING OR RELATING TO SAME AND CERTAIN PRODUCTS CONTAINING SAME

Inv. No. 337-TA-791/826

CONSENT ORDER STIPULATION OF WHALEN MANUFACTURING INC.

WHEREAS, The United States International Trade Commission ("Commission") has instituted the above captioned investigation (the "Investigation") under Section 337 of the Tariff Act of 1930 as amended (19 U.S.C. § 1337), based upon the allegations in the Complaint filed by Twin-Star International Inc. and TS Investment Holding Corp. ("Complainants"), which alleged unfair acts in the importation into the United States, the sale for importation, and the sale within the United States after importation, of certain electric fireplaces, components thereof, manuals for same, certain processes for manufacturing or relating to same and certain products containing same ("Subject Electric Fireplaces") by, among others, Respondent Whalen Furniture Manufacturing Inc. ("Whalen").

Whalen hereby stipulates and agrees as follows:

A. Respondent Whalen is a company organized and existing under the laws of the state of California, with its principal place of business at 1578 Air Wing Road, San Diego, California 92154.

K.W.

B. The Commission has *in rem* jurisdiction over the Subject Electric Fireplaces which are the subject of this Investigation and the Commission has *in personam* jurisdiction over Whalen for the purposes of this Stipulation and Consent Order.

C. Whalen stipulates that it shall not sell for importation, import into the United States, or sell in the United States after importation, or knowingly aid, abet, encourage, participate in, or induce the sale for importation, importation into the United States, or sale in the United States, alone or incorporated with furniture items or other products, (i) any electric fireplace inserts as shown in Attachment A, or manufactured, either directly or indirectly, by Respondent Reliap Industrial Co. ("Reliap") and/or Jason Yue or any entity directly or indirectly associated with Reliap and/or Jason Yue, or that infringe U.S. Copyright Registration No. VA0001772669 or U.S. Copyright Registration No. VA0001772661, or are produced using or which contain misappropriated Twin Star trade secrets; and (ii) any manuals which infringe upon U.S. Copyright Registration No. TX007350474 or U.S. Copyright Registration No. TX0007350476, or any manuals as shown in Attachment B, except under consent or license from the Complainants, their successors, or assigns for a period of time ending five (5) years from the date of the Settlement Agreement attached as Exhibit 3 to the Joint Motion For Termination. Whalen agrees that it cannot promote, sell, market, use and import (or cause to be imported) electric fireplace inserts, alone or incorporated with furniture items or other products, for a period of one (1) year from the date of the Settlement Agreement attached as Exhibit 3 to the Joint Motion to Terminate, except for the electric fireplace inserts

embodying at least all of the characteristics as shown in Attachment C, as well as additional models that embody a curved glass front as part of the facade.

D. Whalen expressly waives all rights to seek judicial review or otherwise challenge or contest the validity of the Consent Order, Attachment D.

E. Whalen will cooperate with and will not seek to impede by litigation or other means the Commission's efforts to gather information under subpart 1 of the Commission's Rules of Practice and Procedure, 19 C.F.R. §210.

F. Enforcement, modification, or revocation of the Consent Order will be carried out pursuant to subpart I of the Commission's Rules of Practice and Procedure, 19 C.F.R. §210.

G. The Consent Order shall not apply with respect to any claim of any intellectual property right that has expired or been found or adjudicated invalid or unenforceable by the Commission or a court or agency of competent jurisdiction, provided that such finding or judgment has become final and nonreviewable.

H. Whalen will not seek to challenge the validity or enforceability of the intellectual property rights set forth in the Complaint for Inv. No 337-TA-826 – *i.e.*, U.S. Copyright Registration Nos. VA0001772661, VA0001772669, TX007350474, TX0007350476 and Complainants' asserted trade secrets (the "Subject Intellectual Property") – in any administrative or judicial proceeding to enforce the Consent Order.

I. Whalen understands and acknowledges that with regard to the information it has provided in the course of discovery in the Investigation, including but not limited to documents, interrogatory responses, and transcripts of sworn deposition

K.W.

testimony, Complainants may seek to introduce such information as evidence in the Investigation after Whalen has been terminated as a respondent. Whalen hereby waives its right to object to, to rebut, or to otherwise address the introduction of such information into the record of the Investigation.

J. Whalen understands and acknowledges that if the Commission enters this Consent Order, Whalen will have waived its right to introduce evidence, cross-examine witnesses, and otherwise participate in the Investigation in any fashion.

K. The signing of this Stipulation and Proposed Consent Order is for settlement purposes only and does not constitute an admission by Whalen that an unfair act has been committed.

L. Other than the Settlement Agreement attached as Exhibit 3 to the Joint Motion to Terminate, there are no agreements, written or oral, express or implied, between Whalen and Complainants concerning the subject matter of the Investigation.

Whalen Furniture Manufacturing, Inc.

Kenneth Whalen
President, Whalen Furniture Manufacturing, Inc.

5-10-12
(Date)

K.W.

ATTACHMENT A

RELIAP

THE MOST RELIABLE FIREPLACE AROUND THE WORLD

23"—Electric Fireplace

Model No.: NW01E

Dimensions: 23.7"W×20"H×8.2"D

Options: Different front decorative trim



REAR DIRECTION MOUNTING



FRONT DIRECTION MOUNTING



FEATURE:

- Can be plugged directly into a standard 120V 60Hz outlet, 1400 Watts
- cUL listed
- 4600BTU, heat up 400 square feet room
- 5000 Hours life time LED light source
- Super infra red remote control
- The most quiet fireplace in industry
- Automatic room temperature control
- Flame brightness adjustable
- Flame and emberbed glow can be on seperately
- Can enjoy the flame effect without heat
- Can install with different front decorative trim
- The most reliable components in industry
- The most realistic flame effect

WDP01285

Copyright©Shenzhen Reliap Industrial Co.,Ltd

Tel:+86 755 29416053 Fax:+86 755 29683019
Website:www.reliap.com

RELIAP

THE MOST RELIABLE FIREPLACE AROUND THE WORLD

23"—Electric Fireplace

Model No: NW02E

Dimensions: 23.7"W×20"H×8.3"D

Options: Different front decorative trim



REAR DIRECTION MOUNTING

FRONT DIRECTION MOUNTING

FEATURE:

- Can be plugged directly into a standard 120V 60Hz outlet, 1400 Watts
- cUL listed
- 4600BTU, heat up 400 square feet room
- 50000 Hours life time LED light source
- Super infra red remote control
- The most quiet fireplace in industry
- Automatic room temperature control
- Flame brightness adjustable
- Flame and emberbed glow can be on seperately
- Can enjoy the flame effect without heat
- Can install with different front decorative trim
- The most reliable components in industry
- The most realistic flame effect

WDP01287

Copyright©Shenzhen Reliap Industrial Co.,Ltd

Tel:+86 755 29610053 Fax:+86 755 29683019
Website:www.reliap.com

RELIAP

THE MOST RELIABLE FIREPLACE AROUND THE WORLD

NW02F ELECTRIC FIREPLACE

Model No.: NW02F

Dimensions: 27"W×22.1"×9.5"D

Opetions: Different front decorative trim



REAR DIRECTION MOUNTING

FRONT DIRECTION MOUNTING

FEATURE

- Can be plugged directly into a standard 120V 60Hz outlet, 1400 Watts
- cUL listed
- 4600BTU, heat up 400 square feet room
- 5000 Hours life time LED light source
- Super infra red remote control
- The most quiet fireplace in industry
- Automatic room temperature control
- Flame brightness adjustable
- Flame and emberbed glow can be on seperately
- Can enjoy the flame effect without heat
- Can install with different front decorative trim
- The most reliable components in industry
- The most realistic flame effect

WDP01288

Copyright©Shenzhen Reliap Industrial Co.,Ltd

Tel:+86 755 29416003 Fax:+86 755 29083019
Website:www.reliap.com

RELIAP

THE MOST RELIABLE FIREPLACE AROUND THE WORLD

30 "ELECTRIC FIREPLACE
MODEL No: NW02H
Dimensions: 31"W× 24"H×9.5"D
Options: Different front decorative trim



REAR DIRECTION MOUNTING

FRONT DIRECTION MOUNTING

FEATURE:

- Can be plugged directly into a standard 120V 60Hz outlet, 1400 Watts
- cUL listed
- 4600BTU, heat up 400 square feet room
- 50000 Hours life time LED light source
- Super infra red remote control
- The most quiet fireplace in industry
- Automatic room temperature control
- Flame brightness adjustable
- Flame and emberbed glow can be on seperately
- Can enjoy the flame effect without heat
- Can install with different front decorative trim
- The most reliable components in industry
- The most realistic flame effect

WDP01289

Copyright©Shenzhen Reliap Industrial Co.,Ltd

Tel:+86 755 29415053 Fax:+86 755 29683019
Website:www.reliap.com

RELIAP

THE MOST RELIABLE FIREPLACE AROUND THE WORLD

NW22F ELECTRIC FIREPLACE

Model No.: NW22F

Dimensions: 27"W×17.6"H×9.5"D

Options: Different front decorative trim



REAR DIRECTION MOUNTING



FRONT DIRECTION MOUNTING



FEATURE

- Can be plugged directly into a standard 120V 60Hz outlet, 1400 Watts
- cUL listed
- 4600BTU, heat up 400 square feet room
- 50000 Hours life time LED light source
- Super infra red remote control
- The most quiet fireplace in industry
- Automatic room temperature control
- Flame brightness adjustable
- Flame and emberbed glow can be on seperately
- Can enjoy the flame effect without heat
- Can install with different front decorative trim
- The most reliable components in industry
- The most realistic flame effect

WDP01290

Copyright©Shenzhen Reliap Industrial Co.,Ltd

Tel:+86 755 29416053 Fax:+86 755 29683019
Website:www.reliap.com


19”
1.38”
18”
WDP01286
18”
7”

ATTACHMENT B

ELECTRIC FIREPLACE

VENT FREE FIREPLACE WITH HEATER

HOMEOWNERS OPERATING MANUAL

MODELS: FP-30-1 / FP-26-1 / FP- 26-2
FP-23-1 / FP-18-1

CONSUMER SAFETY INFORMATION

PLEASE READ THIS MANUAL BEFORE

INSTALLING AND OPERATING THIS APPLIANCE

⚠ WARNING

IF THE INFORMATION IN THIS MANUAL IS NOT FOLLOWED,

AN ELECTRIC SHOCK OR FIRE MAY RESULT IN PROPERTY DAMAGE,

PERSONAL INJURY, OR LOSS OF LIFE.

Thank you and congratulations on your purchase of a Whalen fireplace. Please read the Installation Instructions before using this appliance.

IMPORTANT: Read all instructions and warnings carefully before starting installation. Failure to follow these instructions may result in a possible electric shock, fire hazard, and/or injury and will void the warranty.

For Customer Service:

1-866-942-5362
Pacific Standard Time:8:30 a.m.-4:30 p.m.,Monday - Friday
Or visit our web site 24 hours a day,7 days a week for product assistance at
www.whalenfurniture.com
Or e-mail your request to **parts@whalenfurniture.com**

Whalen Furniture Mfg ., Inc
Made in China
Printed in China

INSTRUCTION MANUAL

When using electrical appliances, basic precautions should always be followed to reduce the risk or fire, electrical shock, and/or injury including the following:

1. Read all instructions before using this appliance.
2. This appliance is hot when in use. To avoid burns, do not let bare skin touch hot surfaces. If provided, use handles when moving this appliance.
   ⚠ DANGER High temperatures may be generated under certain abnormal conditions. Do not partially or fully cover or obstruct the front of the heater.
   ⚠ WARNING In order to avoid overheating, do not cover the heater. It cannot be used in a closet.
3. **⚠ CAUTION** The appliance should not be used by children or persons with reduced physical, sensory or mental capabilities.
4. Children should be advised not to play with the appliance.
5. Always unplug this appliance when not in use.
6. Do not operate any heater with a damaged cord or plug or after the appliance malfunctions, or if it has been dropped or damaged in any manner.
7. If the supply cord is damaged, it must be replaced by the manufacturer, it's service agent or similarly qualified persons in order to avoid a hazard.
8. Any repairs to this fireplace should be carried out by a qualified service person.
9. Under no circumstances should this fireplace be modified. Parts having to be removed for servicing must be replaced prior to operating this fireplace again.
10. Do not use outdoors.
11. This heater is not intended for use in bathrooms, laundry areas and similar indoor locations. Never locate this appliance where it may fall into a bathtub or other water container.
12. Do not run cord under carpeting. Do not cover cord with throw rugs, runners or the like. Arrange cord away from traffic areas and where it will not be tripped over.
13. To disconnect this appliance, turn controls to the off position, then remove plug from outlet.
14. Connect to properly grounded outlets only.
15. This appliance, when installed, must be electrically grounded in accordance with local codes or, in the absence of local codes, with the current CSA C22.1 Canadian Electrical Code or for U.S.A. Installations, follow local codes and the National Electrical Code, ANSI/NFPA NO 70.
16. **There is a protective thermostat limiter inside the heater. When the inner temperature over heats, the thermostat limiter will shut off the power supply to avoid the risk of fire damage to the appliance.**
17. The heaters must not be located immediately below a socket-outlet.
18. Do not insert or allow foreign objects to enter any ventilation or exhaust opening as this may cause an electric shock or fire, or damage the appliance.
19. To prevent a possible fire, do not block air intakes or exhaust in any manner. Do not use on soft surfaces, like a bed, where opening may become blocked.
20. This appliance has hot and arcing or sparking parts inside. Do not use where gasoline, paint, or flammable liquids are used or stored. This fireplace should not be used as a drying rack for clothing. Christmas stockings or decorations should not be hung in the area of it.
21. Use this appliance only as described in the manual. Any other use not recommended by the manufacturer may cause fire, electric shock or injury to persons.
22. Always plug heaters directly into a wall outlet/receptacle. Never use with an extension cord or reloadable power tap (outlet/power strip).
23. See Figure 1 for the follow directions.
    This heater is for use on 120 volts. The cord has a plug as shown in figure 1.See Figure 1 for grounding instruction. An adapter as shown at C is available for connecting three-blade grounding type plugs to two-slot receptacles. The green grounding plug extending from the adapter must be connected to a permanent ground such as a properly grounded outlet box. The adapter should not be used if a three-slot grounded receptacle is available.

FIGURE 1



SAVE THESE INSTRUCTIONS

PARTS LIST

Part Name	FP-30-1	FP-26-1	FP-26-2	FP-23-1	FP-18-1
Ember Bed / Logs	√	√	√	√	√
Heater	√	√	√	√	√
Blower	√	√	√	√	√
Down Light	√	√			
Main PCB	√	√	√	√	√
Control Panel PCB	√	√	√	√	√
Flame Generator Drive Motor	√	√	√	√	√
Flame Light PCB	√	√	√	√	√
Logs Light PCB	√	√	√	√	√
Ember Bed Light PCB	√	√	√	√	√
Remote Control-4 Buttons	√	√	√	√	√

Cold climate installation recommendation:
When installing this unit against a Non-insulated exterior wall or chase, it is Mandatory that outer walls be insulated to Conform to applicable insulation codes.

ELECTRICAL SPECIFICATIONS

Voltage: 120 VAC, 60 Hz

Watts: 1400 Watts

ELECTRICAL CONNECTION

The unit comes standard with 6 feet (1.8m) three wire cord, exiting from the rear of the fireplace. Plan the installation to avoid the use of an extension cord. If an extension cord must be used, it must be a minimum 16 AWG; three wires with grounding type plug connection and rated not less than 1875 Watts The cord shall not be more than 20 feet (6m) in length.

CLEANING TRIM

Clean the metal trim using a soft cloth, slightly dampened with citrus oil based product and buff With a clean soft cloth. **DO NOT** use brass polish or household cleaners as these products will damage the metal trim. Citrus oil based products can be obtained at supermarkets or hardware stores.

MAINTENANCE

The motors used on the fan and the flame generator assembly are pre-lubricated for extended bearing life and require no further lubrication. However, periodic cleaning/vacuuming of the fan/heater unit is recommended. Make sure the unit is turn OFF and unplugged whenever you are cleaning the heater or fireplace.

⚠ WARNING Make sure the power is turned off before proceeding. Any electrical repairs or rewiring of this unit should be carried out by a licensed electrician in accordance with national and local codes. If repairing or replacing any electrical component or wiring, the original wire routing, color coding and securing locations must be followed.

⚠ WARNING Electric outlet wiring must comply with local building codes and other applicable regulations to reduce the risk of fire, electrical shock and injury to persons.

⚠ WARNING Do not use this fireplace if any part of it has been under water. Immediately call a qualified service technician to inspect the fireplace and replace any part of the electrical system.

⚠ WARNING Disconnect power before attempting any maintenance or cleaning to reduce the risk of fire, electrical shock or personal injury.

⚠ WARNING During any service of this appliance, the power to the unit must be turned off. First turn the main power switch to the "OFF" position. Then remove the electrical plugfrom the wall outlet.

OPERATING INSTRUCTIONS·CONTROL FUNCTION

CONTROL PANEL ACCESS

Control panel can be accessed at upper-right corner of appliance

OPERATION INSTRUCTIONS WITHOUT REMOTE



POWER

The POWER button turns the appliance on or off. It has a memory function; the button turns off all functions at once but retains the settings in the memory. By pressing the button again, the unit will turn on at the same settings. If the TIMER has been set & time has expired all functions will stop. Press the POWER button start the appliance.

FLAME

The FLAME control switch manages the flame brightness. There are 4 brightness levels and an off position. Each time the FLAME button is pressed, the intensity of the flame decreases. When adjusting the FLAME button, a number indicating the brightness of flame will be visible on the digital display. After turning on digital display, if nothing happens within 10 seconds, digital display will turn off. There is a down light over the ember bed. When the FLAME button is in the ON position, down light will turn on, it will turn off in OFF position.

The FLAME button has locking function. Press the FLAME button for 5 seconds. The down light will turn off. When the ember bed light flashes 6 times, it is confirming the flame function is locked. To remove locking function press FLAME button for 5 seconds, the ember bed light will flash 6 times, both the flame light and ember bed will be on.

HEATER

The HEATER button turns the heater on and off. When in ON position, press the HEATER button 5 seconds and enter temperature adjustment mode. In the adjustment mode, the digital indicator will flash at .05 second intervals. There are 23 temperature settings: 72℉—73℉—74℉…82℉—ON—62℉—63℉—64℉…71℉(22℃—23℃—24℃…27℃-ON—17℃—18℃…21℃). After the temperature is selected the digital indicator will flash 5 times and will exit from setting status. After turning on the digital temperature display, if nothing happens within 10 seconds, digital display will expire.

Temperature Switch Function: With the HEATER in the ON position, press the POWER button for 5 seconds, current temperature indicator will flash 3 times; after that it will switch to another temperature.

This button has a locking function. Press the HEATER button for 10 seconds, the ember bed light will flash 6 times, indicating that the HEATER function is locked. To remove locking the function press the HEATER button 10 seconds the ember bed light will flash 6 times, indicating the locking function has been removed. Press HEATER button again, and the heating function will resume.

TIMER

The TIMER has adjustable settings at 30 minute intervals. After turning on the digital display if nothing happens for 10 seconds the display will shut off. After the desired (set) time has expired the TIMER indicator light will flash 6 times and all functions will stop. All appliance settings EXCEPT the TIMER will be retained in the memory.

After entering the time setting press the power button to remove the setting function and retain in the memory.

OPERATION INSTRUCTIONS WITH REMOTE

POWER

The POWER button turns the appliance on and off.It has a memory function; the button turns off all functions at once but retains settings in the memory.

FLAME

The FLAME button manages the flame brightness. Each time the FLAME button is pressed the intensity of the flame decreases. There are four brightness levels you can cycle through including the OFF setting. When adjusting the FLAME button a number will appear on the digital display indicating the brightness of the flame. The FLAME button does not have a locking or unlocking function.

HEATER

The HEATER button turns the heater on and off. When pressing HEATER button on the remote, the default setting temperature is 72°F(22°C).The HEATER button does not have locking or remove locking function.

TIMER

The timer may be adjusted at 30 minute intervals. The temperature setting will be visible on the digital display.

NOTE: This equipment has been tested and found to comply with the limits for Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and the receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

⚠CAUTION This remote control uses 1 CR2032 lithium button cell battery (included) Never dispose of batteries in fire, except under conditions of controlled incineration. Failure to observe this precaution may result in an explosion.



This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

1) This device may not cause harmful interference.
2) This device must accept any interference received, including interference that may cause undesired operation.

Modifications not approved by the party responsible for compliance could void user's authority to operate the equipment.

This Class B digital apparatus complies with Canadian ICES-003.

TROUBLE SHOOTING GUIDE

MODELS: FP-30-1 / FP-26-1 / FP-26-2 FP-23-1 / FP-18-1

PROBLEM	SOLUTION
1. No power or function.	1a.Check that unit is plugged into a standard 120V wall outlet. 1b.Press power button on the control panel.
2. Main power switch lights up, but no flame effect.	2a. Open the top and back panel to check if the flame spindle has fallen off from spindle motor.
3. Have flame effect, but heater does not blow warm air.	3a. Confirm temperature setting exceeds room temperature. 3b. Try to turn on/off HEATER button several times to make sure it is in the "ON" position.
4. Heater does not work, but Power and Heater switches are in the "ON" position and thermostat is set on "HI".	4a. Turn all switches to the "OFF" position and unplug the unit from the wall outlet for 5 minutes. After 5 minutes plug the unit back into wall outlet, and operate as normal.

1 YEAR LIMITED WARRANTY

Electric Fireplaces

BASIC WARRANTY

Whalen Electric Fireplace is free from manufacturing and material defects for a period of one year from date of purchase, subject to the following conditions and limitations

1. This electric fireplace must be installed and operated at all times in accordance with the installation and operating instructions furnished with the product. Any unauthorized repair, alteration, willful abuse, accident, or misuse of the product shall nullify this warranty.
2. This warranty is non-transferable, and is made to the original owner, provided that the purchase was made through an authorized supplier of the company.
3. The warranty is limited to the repair or replacement of part(s) found to be defective in material or workmanship, provided that such part(s) have been subjected to normal conditions of use and service, after said defect is confirmed by the Company's inspection.
4. The Company may, at its discretion, fully discharge all obligations with respect to this warranty by refunding the wholesale price of the defective part(s).
5. Any installation, labor, construction, transportation, or other related costs/expenses arising from defective part(s), repair, replacement, or otherwise of same, will not be covered by this warranty, nor shall the Company assume responsibility for same.
6. The owner/user assumes all other risks, if any, including the risk of any direct, indirect or consequential loss or damage arising out of the use, or inability to use the product, except as provided by law.
7. All other warranties - expressed of implied – with respect to the product, its components and accessories, or any obligations/liabilities on the part of the Company are hereby expressly excluded.
8. The Company neither assumes, nor authorizes any third party to assume, on its behalf, any other liabilities with respect to the sale of the Whalen product.
9. The warranties as outlined within this document do not apply to non Whalen accessories used in conjunction with the installation of this product. This warranty is void if:

a. The fireplace is subjected to prolonged periods of dampness or condensation.
b. Any unauthorized alteration, willful abuse, accident, or misuse of the product.
c. You do not have the original receipt of purchase.

IF WARRANTY SERVICE IS NEEDED

Contact the company, at parts@whalenfurniture.com Or call 1-866-942-5362. Make sure you have your warranty, your sales receipt, location of purchase and the model/serial number of your Whalen products.

For update and revisions to this manual
Please see our website
www.whalenfurniture.com

Whalen Furniture Mfg ., Inc
Made in China
Printed in China

CHIMENEA ELÉCTRICA

CHIMENEA SIN RESPIRADERO CON CALENTADOR

MANUAL DE OPERACIÓN DEL PROPIETARIO

MODELOS: FP-30-1 / FP- 26-1 / FP-26-2
FP-23-1 / FP-18-1

NFORMACIÓN DE SEGURIDAD PARA EL CONSUMIDOR

LEA ESTE MANUAL ANTES DE INSTALAR Y OPERAR ESTE APARATO

⚠ ADVERTENCIA

EN CASO DE NO SEGUIR LA INFORMACIÓN EN ESTE MANUAL, UNA DESCARGA ELÉCTRICA O UN INCENDIO PUEDE PROVOCAR DAÑOS A LA PROPIEDAD, LESIONES PERSONALES O LA PÉRDIDA DE LA VIDA.

Gracias y felicitaciones por la adquisición de una chimenea Whalen. Lea las Instrucciones de Instalación antes de utilizar este aparato.

IMPORTANTE: Antes de comenzar la instalación, lea detenidamente todas las instrucciones y advertencias. El incumplimiento de estas instrucciones podría provocar una posible descarga eléctrica, riesgo de incendio, y/o lesiones y anulará la garantía.

Para el servicio a la clientela :

1-866-942-5362
Hora Estandar del Pacífico:8:30 am – 4:30 pm de Lunes a Viernes
O visite nuestra página de Internet 24 horas al dia, 7 días de la semana para ayuda en su producto
En: **www.whalenfurniture.com**
O mande un correo eléctronico a **parts@whalenfurniture.com**

Whalen Furniture Mfg ., Inc
Hecho en China
Impreso en China

MANUAL DE INSTRUCCIONES

Al utilizar aparatos eléctricos, siempre deberán tomarse precauciones básicas para disminuir el riesgo de incendio, descarga eléctrica y/o lesiones, incluyendo lo siguiente:

1. Lea todas las instrucciones antes de usar este aparato
2. Este aparato se calienta cuando está en uso. Para evitar quemaduras, no permita que la piel sin protección toque superficies calientes. Si existen, utilice las asas al mover este aparato.
   ⚠ PELIGRO Bajo determinadas condiciones anormales, se pueden generar altas temperaturas. No cubra ni obstruya parcial ni completamente el frente del calentador.
   ⚠ ADVERTENCIA Para evitar sobrecalentamiento, no cubra el calentador. El mismo no puede utilizarse en un closet.
3. **⚠ PRECAUCIÓN** El aparato no debe ser utilizado por niños ni por personas con capacidades físicas, sensoriales o mentales reducidas.
4. Se deben avisar a los niños que no jueguen con el calentador.
5. Desconecte siempre este aparato cuando no esté en uso.
6. No utilice ningún calentador con cables o enchufes dañados ni después de que el aparato haya tenido un mal funcionamiento, se haya caído o dañado de cualquier manera.
7. Si el cable de alimentación de corriente está dañado, debe ser reemplazado por el fabricante, su agente de servicio u otra persona con las mismas calificaciones para prevenir los accidentes.
8. Todas las reparaciones a esta chimenea deberán ser realizadas por una persona calificada de mantenimiento.
9. Bajo ninguna circunstancia deberá modificarse esta chimenea. Las piezas que se tengan que retirar para la reparación se deben reemplazar antes de poner a funcionar esta chimenea de nuevo.
10. No lo use en exteriores.
11. Este calentador no está diseñado para usarse en baños, áreas de lavado ni en lugares interiores similares. Nunca coloque este electrodoméstico en lugares donde se pueda caer dentro de una bañera u otro recipiente con agua.
12. No coloque el cable debajo de una alfombra. No cubra el cable con tapetes, alfombras de pasillo o cubiertas similares. Coloque el cable lejos de las zonas de tránsito, donde nadie se pueda tropezar y caer.
13. Para desconectar este aparato, coloque los controles en la posición de apagado, y luego retire el enchufe del tomacorriente.
14. Solamente conecte el aparato a tomacorrientes que estén debidamente conectados a tierra.
15. Al instalar este aparato, deberá tener una conexión eléctrica a tierra de acuerdo con los códigos locales o, en ausencia de códigos locales, con el Código de Electricidad Canadiense vigente norma CSA C22.1 o para las instalaciones en EE.UU., siga los códigos locales y el Código Nacional de Electricidad, ANSI/NFPA NO.70.
16. **El calentador tiene un termostato limitador en su interior. Cuando la temperatura interna sube demasiado o se produce un calentamiento anormal, el dispositivo de protección del termostato corta el suministro de energía para evitar que la chimenea se dañe o se produzca riesgo de incendio.**
17. Los calentadores no pueden colocarse inmediatamente debajo de un tomacorriente.
18. No inserte ni permita que entren objetos extraños a las aperturas de ventilación o de extracción, ya que esto puede ocasionar una descarga eléctrica, un incendio o puede dañar el calentador.
19. A fin de evitar un posible incendio, no bloquee las entradas ni las salidas de aire de manera alguna. No lo coloque sobre superficies suaves, como una cama, donde podrían bloquearse las aberturas.
20. Este aparato tiene piezas calientes y piezas que producen arcos eléctricos o chispas en su interior. No lo utilice en áreas donde se use o guarde gasolina, pintura u otros líquidos inflamables. Esta chimenea no debe utilizarse como un soporte para secar ropa. No deben colgarse medias para los regalos de Navidad ni elementos decorativos cerca del aparato.
21. Utilice este aparato únicamente como se describe en el manual. Cualquier otro uso no recomendado por el fabricante puede ocasionar incendio, descarga eléctrica o lesiones a personas.
22. Siempre enchufe los calentadores directamente en un receptáculo o tomacorriente de pared. Nunca lo use con una extensión o un contacto múltiple con tomas reubicables (tomacorriente/enchufe múltiple).
23. Vea la Figura 1 para consultar las indicaciones a seguir. Este calentador debe utilizarse con 120 voltios. El cable incluye un enchufe tal como se muestra en la Figura 1. Vea las instrucciones de conexión a tierra en la Figura 1. Hay un adaptador, como se ilustra en C, disponible para conectar enchufes de conexión a tierra de tres clavijas en receptáculos de dos ranuras. El enchufe verde de conexión a tierra que se extiende desde el adaptador debe conectarse a una toma de tierra permanente, como la de una caja de tomacorriente correctamente conectada a tierra. No es necesario utilizar el adaptador si hay un receptáculo de tres ranuras conectado a tierra.

FIGURA 1

GUARDE ESTAS INSTRUCCIONES

LISTA DE PIEZAS

Nombre de la Pieza	FP-30-1	FP-26-1	FP-26-2	FP-23-1	FP-18-1
Lecho de brasas / Los registros	√	√	√	√	√
Conjunto de calentador	√	√	√	√	√
Ventilador	√	√	√	√	√
Abajo se enciende	√	√			
PCB (Conjunto de placa de circuito impreso) principal	√	√	√	√	√
PCB del panel de control	√	√	√	√	√
Motor de accionamiento del generador de llama	√	√	√	√	√
PCB ligero de la llama	√	√	√	√	√
PCB ligero de los registros	√	√	√	√	√
PCB ligero de lecho de brasas	√	√	√	√	√
Mando a distancia-4 botones	√	√	√	√	√

Recomendación para la instalación en climas fríos:
Al instalar esta unidad contra un compartimiento o un pared exterior sin aislamiento, es obligatorio aislar las paredes externas conforme con los códigos de aislamiento correspondientes

ESPECIFICACIONES ELÉCTRICAS
Voltaje: 120 VAC, 60 Hz
Vatios: 1400 Vatios

CONEXIÓN ELÉCTRICA

La unidad viene estándar con un cable trifilar de 6 pies (1,8 m) que sale de la parte trasera de la chimenea. Planifique la instalación para evitar el uso de un cable de extensión. Si fuera necesario usar un cable de extensión, éste deberá ser como mínimo No. 16 AWG; trifilar con conector de enchufe de conexión a tierra y clasificación no inferior a 1875 vatios. El cable no deberá tener más de 20 pies (6 m) de longitud.

LIMPIEZA DE LA MOLDURA

Limpie la moldura metálica con un paño suave, ligeramente humedecido con un producto a base de aceite cítrico y púlalo con un paño suave y limpio. NO utilice productos de limpieza domésticos ni limpiametales, ya que estos productos dañarán la moldura metálica. Los productos a base de aceite cítrico pueden conseguirse en supermercados o ferreterías.

MANTENIMIENTO

Los motores que se utilizan en el ventilador y el conjunto generador de llama están prelubricados para prolongar la vida útil de los cojinetes y no es necesario lubricarlos más. Sin embargo, se recomienda limpiar/aspirar la unidad del ventilador/calentador. Asegúrese de que la unidad está **APAGADA** y **desenchufada** cuando esté limpiando el calentador o la chimenea

⚠ ADVERTENCIA Asegúrese de que la alimentación eléctrica esté desconectada antes de continuar. Toda reparación o renovación del sistema eléctrico de esta unidad deberá ser realizada por un electricista autorizado de acuerdo con códigos nacionales y locales. En caso de reparar o cambiar cualquier componente eléctrico, deberá seguirse la ruta de cables, el código de colores y los lugares de sujeción originales

⚠ ADVERTENCIA El cableado del tomacorriente eléctrico tiene que cumplir con los códigos de construcción locales y otras normas aplicables, a fin de reducir el riesgo de incendio, descarga eléctrica y lesiones a personas.

⚠ ADVERTENCIA No utilice esta chimenea si alguna de sus piezas ha estado sumergida en agua. Llame inmediatamente a un técnic de mantenimiento calificado para que inspeccione la chimenea y cambie cualquier pieza del sistema eléctrico.

⚠ ADVERTENCIA Desconecte la alimentación eléctrica antes de intentar realizar mantenimiento o limpieza para reducir el riesgo de incendio, descarga eléctrica o lesiones personales.

⚠ ADVERTENCIA Durante el mantenimiento de este aparato, deberá desconectarse la corriente a la unidad. Primero, coloque el interruptor de alimentación principal en la posición "APAGADO" ("OFF"). Luego, retire el enchufe eléctrico del tomacorriente de pared.

INSTRUCCIONES DE OPERACIÓN · FUNCIONES DE LOS

ACCESO AL PANEL DE CONTROL

Se puede tener acceso al panel de control por la esquina superior derecha del aparato.

INSTRUCCIONES DE OPERATION SIN CONTROL REMOTO



ENERGÍA

El botón de ENERGÍA enciende y apaga el aparato. El equipo tiene una función de memoria; el botón apaga todas las funciones a la vez, pero retiene los ajustes en la memoria. Al presionar el botón otra vez, la unidad se encenderá nuevamente con los mismos ajustes. Si se ha ajustado el TEMPORIZADOR y el tiempo se ha vencido, todas las funciones se detendrán. Presione el botón de ENERGÍA para encender el aparato.

LLAMA

El interruptor de control de la LLAMA controla la brillantez de la llama.Hay 4 niveles de brillantez y una posición de apagado. Cada vez que se presiona el botón LLAMA, la intensidad de la llama disminuye. Al ajustar el botón LLAMA, aparecerá en la pantalla digital un número indicando el grado de brillantez de la llama.Después de encender la pantalla digital,si no sucede nada en 10 segundos, se apagará la pantalla digital. Hay una luz hacia abajo que ilumina el lecho de brasas.Cuando el botón LLAMA se coloca en la posición ENCENDIDO,se encenderá la luz de emisión hacia abajo,y se apagará en la posición APAGADO.
El botón de la LLAMA también tiene una función de bloqueo. Presione el botón LLAMA durante 5 segundos. La luz de emisión hacia abajo se apagará. Cuando la luz del lecho de brasas destelle 6 veces, está confirmando que la función de llama está bloqueada.
Para quitar la función de bloqueo, presione el botón LLAMA durante 5 segundos, la luz del lecho de brasas destellará 6 veces, indicándole que la luz de llama y del lecho de brasas se encenderán

CALENTADOR

El botón del CALENTADOR enciende y apaga el calentador. Cuando está en la posición ENCENDIDO, presione el botón del CALENTADOR 5 segundos y seleccione la modalidad de ajuste de temperatura. En la modalidad de ajuste,el indicador digital destellará a intervalos de 0.05 segundos.Hay 23 ajustes temperatura: 72℉—73℉—74℉…82℉—ENCENDIDO—62℉—63℉—64℉…71℉(22℃—23℃—24℃…27℃- ENCENDIDO —17℃—18℃…21℃). Una vez que haya seleccionado la temperatura, el indicador digital destellará 5 veces y saldrá de la modalidad de ajuste. Después de encender la pantalla digital de temperatura, si no sucede nada en 10 segundos, se apagará la pantalla digital.
Función de cambio de temperatura: Con el CALENTADOR colocado en la posición ENCENDIDO, presione el botón de ENERGÍA durante 5 segundos, el indicador de la temperatura actual destellará 3 veces; después de lo cual cambiará a otra temperatura.
Este botón tiene una función de bloqueo. Presione el botón CALENTADOR durante 10 segundos, la luz del lecho de brasas destellará 6 veces, indicando que la función de CALENTADOR está bloqueada. Para quitar la función de bloqueo, presione el botón CALENTADOR 10 segundos y la luz del lecho de brasas destellará 6 veces, indicándole que se ha quitado la función de bloqueo. Presione nuevamente el botón CALENTADOR, y la función de calentamiento continuará funcionando.

TIMER

IEl TEMPORIZADOR tiene ajustes que se pueden regular a intervalos de 30 minutos. Después de encender la pantalla digital, si no sucede nada en10 segundos, se apagará la pantalla digital. Después que haya terminado el tiempo deseado (ajustado), la luz indicadora del TEMPORIZADOR destellará 6 veces y todas las funciones se detendrán. Todos los ajustes del aparato EXCEPTO el TEMPORIZADOR se mantendrán en la memoria.
Después de poner el tiempo deseado, presione el botón de energía para salir de la función de ajuste y mantener el tiempo en la memoria.

INSTRUCCIONES DE OPERACIÓN CON CONTROL REMOTO

ENERGÍA

El botón de ENERGÍA enciende y apaga el aparato. El equipo tiene una función de memoria; el botón apaga todas las funciones a la vez, pero retiene los ajustes en la memoria.

FLAME

El botón de LLAMA controla la brillantez de la llama. Cada vez que se presiona el botón LLAMA, la intensidad de la llama disminuye. Hay cuatro niveles de brillantez que usted puede utilizar incluso la opción de APAGADO. Al ajustar el botón LLAMA, aparecerá en la pantalla digital un número indicando el grado de brillantez de la llama. El botón LLAMA no tiene una función de bloqueo o desbloqueo.

HEATER

El botón CALENTADOR enciende y apaga el calentador. Al presionar el botón CALENTADOR en el control remoto, la temperatura predeterminada de fábrica es 72°F (22°C). El botón CALENTADOR no tiene una función de bloqueo o desbloqueo.

TIMER

El temporizador puede ajustarse a intervalos de 30 minutos. El ajuste de temperatura aparecerá en la pantalla digital.

NOTA: Este equipo ha sido probado, determinándose que cumple con los límites establecidos para un dispositivo digital de clase B, de acuerdo con la Parte 15 de las Normas de la FCC. Estos límites han sido diseñados para brindar una protección razonable contra la interferencia dañina en una instalación residencial. **Este equipo genera, utiliza, y puede irradiar energía de radiofrecuencia y, en caso de no ser instalado y utilizado de acuerdo con las instrucciones, puede causar interferencias dañinas a la recepción de radio y televisión, lo cual se puede determinar apagando y encendiendo el equipo. Le recomendamos al usuario que intente corregir la interferencia con una o más de las siguientes medidas:**

- Reorientar o reubicar la antena receptora.
- Aumentar la distancia entre el equipo y el receptor.
- Conectar el equipo a un tomacorriente en un circuito diferente al que el receptor está conectado.
- Consultar al distribuidor o alqún técnico de radio/TV con experiencia.

⚠PRECAUCIÓN Este control remoto utiliza 1 batería CR2032 de iones de litio tipo botón (Incluida). Nunca deseche las baterías en el fuego, excepto en condiciones de incineración controlada. Si no se obedece esta precaución, podría producirse una explosión



Este dispositivo cumple con lo dispuesto en la Parte 15 de las Normas de la Comisión Federal de Comunicaciones (FCC por sus siglas en inglés). Su funcionamiento se encuentra sujeto a las dos condiciones siguientes:

1) Este dispositivo no puede ocasionar interferencia dañina.
2) Este dispositivo debe aceptar cualquier interferencia recibida, incluyendo la interferencia que pueda ocasionar un funcionamiento indeseable.

Las modificaciones que no estén aprobados por la parte responsable de su aceptación podrían anular el derecho del usuario para operar el equipo.Este aparato digital de Clase B cumple con la norma canadiense ICES-003.

GUÍA DE LOCALIZACIÓN Y SOLUCIÓN DE PROBLEMAS

MODELOS: FP-30-1 / FP-26-1 / FP-26-2
FP-23-1 / FP-18-1

PROBLEMA	SOLUCIÓN
1. No hay energía o no funciona.	1a.Compruebe que la unidad esté enchufada a un tomacorriente estándar de 120V. 1b.Presione el botón de energía en el panel de control.
2. Los interruptores principales se encienden, pero no hay efecto de llama.	2a. Abra el panel superior y trasero para comprobar si el husillo de la llama se ha zafado del motor de husillo.
3. El efecto de llama funciona, pero el calentador no echa aire caliente.	3a. Asegúrese de que el ajuste de temperatura sea superior a la temperatura ambiente. 3b. Trate de encender y apagar el botón CALENTADOR varias veces para asegurarse de que esté en la posición 'ENCENDIDO".
4. El calentador no funciona, pero los interruptores Energía (Power) y Calentador (Heater) están en la posición "ENCENDIDO" ("ON") y el termostato está ajustado en "ALTA" ("HI").	4a. Coloque todos los interruptores en la posición "APAGADO" ("OFF") y desenchufe la unidad del tomacorriente de la pared durante 5 minutos. Luego de 5 minutos, enchufe nuevamente la unidad al tomacorriente de la pared, y opérela de la manera habitual.

GARANTÍA LIMITADA DE 1 AÑO

Chimeneas Eléctricas

GARANTÍA BÁSICA

La Chimenea Eléctrica Whalen está libre de defectos de fabricación y materiales, durante un período de un año a partir de la fecha de compra, sujeto a las siguientes condiciones y limitaciones.

1. Esta chimenea eléctrica tiene que instalarse y operarse en todo momento de acuerdo con las instrucciones de instalación y funcionamiento suministradas con el producto. Toda reparación, alteración, maltrato intencionado, accidente, o mala utilización del producto que no esté autorizada anulará esta garantía.
2. Esta garantía no es transferible y se otorga al propietario original, siempre y cuando la compra se haya realizado a través de un proveedor autorizado de la compañía.
3. La garantía está limitada a la reparación o el reemplazo de piezas que se hayan encontrado defectuosas en relación con la mano de obra o el material, siempre y cuando estas piezas hayan sido sometidas a condiciones normales de uso y mantenimiento, luego de que dicho defecto haya sido confirmado por la inspección de la Compañía.
4. Según su criterio, la Compañía podrá cumplir con todas las obligaciones con respecto a esta garantía al reembolsar el precio mayorista de las piezas defectuosas.
5. ATodos los costos de instalación, mano de obra, construcción, transporte u otros gastos que surjan de las piezas defectuosas, la reparación, el reemplazo, o similares no estarán cubiertos por esta garantía, ni la Compañía asumirá la responsabilidad de éstos.
6. El propietario/usuario asume todos los demás riesgos, si los hay, que incluyen el riesgo de cualquier pérdida o daño directo, indirecto o resultante que surja del uso o la incapacidad para usar el producto, a excepción de lo dispuesto por ley.
7. Por la presente se excluyen expresamente todas las otras garantías, ya sean explícitas o implícitas, con respecto al producto, sus componentes y accesorios, o cualquier obligación/responsabilidad por parte de la Compañía.
8. La Compañía no asume, ni autoriza a ningún tercero a asumir en su nombre, ninguna otra responsabilidad con respecto a la venta del producto Whalen.
9. Las garantías tal como se describen en este documento no se aplican a accesorios que no sean de Whalen que se utilicen en conjunto con la instalación de este producto. Esta garantía no tendrá validez si:
   a. La chimenea es sometida a períodos prolongados de humedad o condensación.
   b. Toda alteración, maltrato intencionado, accidente, o mala utilización del producto que no esté autorizada.
   c. Usted no tiene el recibo original de compra.

SI NECESITA EL SERVICIO DE LA

Asegúrese de tener la garantía, el recibo de venta, el lugar de la compra y el número de modelo/serie de su Chimenea Whalen.

Whalen Furniture Mfg ., Inc
Hecho en China
Impreso en China

ELECTRIC FIREPLACE

VENT FREE FIREPLACE WITH HEATER

HOMEOWNERS OPERATING MANUAL

MODEL： FP-30-1

CONSUMER SAFETY INFORMATION

PLEASE READ THIS MANUAL BEFORE

INSTALLING AND OPERATING THIS APPLIANCE

⚠ WARNING

IF THE INFORMATION IN THIS MANUAL IS NOT FOLLOWED,

AN ELECTRIC SHOCK OR FIRE MAY RESULT IN PROPERTY DAMAGE,

PERSONAL INJURY, OR LOSS OF LIFE.

Thank you and congratulations on your purchase of a Whalen fireplace. Please read the Installation Instructions before using this appliance.

IMPORTANT: Read all instructions and warnings carefully before starting installation. Failure to follow these instructions may result in a possible electric shock, fire hazard, and/or injury and will void the warranty.

For Customer Service:

00-1-866-942-5362
Pacific Standard Time:8:30 a.m.-4:30 p.m.,Monday - Friday
Or visit our web site 24 hours a day,7 days a week for product assistance at
www.whalenstyle.com
Or e-mail your request to **parts@whalenfurniture.com**

ATTENTION

Also Requires

Wood Fireplace Mantel

Whalen Furniture Mfg ., Inc
Made in China
Printed in China

INSTRUCTION MANUAL

When using electrical appliances, basic precautions should always be followed to reduce the risk or fire, electrical shock, and/or injury including the following:

1. Read all instructions before using this appliance.
2. This appliance is hot when in use. To avoid burns, do not let bare skin touch hot surfaces. If provided, use handles when moving this appliance.
   ⚠ DANGER High temperatures may be generated under certain abnormal conditions. Do not partially or fully cover or obstruct the front of the heater.
   ⚠ WARNING In order to avoid overheating, do not cover the heater. It cannot be used in a closet.
3. **⚠ CAUTION** The appliance should not be used by children or persons with reduced physical, sensory or mental capabilities.
4. Children should be advised not to play with the appliance.
5. Always unplug this appliance when not in use.
6. Do not operate any heater with a damaged cord or plug or after the appliance malfunctions, or if it has been dropped or damaged in any manner.
7. If the supply cord is damaged, it must be replaced by the manufacturer, it's service agent or similarly qualified persons in order to avoid a hazard.
8. Any repairs to this fireplace should be carried out by a qualified service person.
9. Under no circumstances should this fireplace be modified. Parts having to be removed for servicing must be replaced prior to operating this fireplace again.
10. Do not use outdoors.
11. This heater is not intended for use in bathrooms, laundry areas and similar indoor locations. Never locate this appliance where it may fall into a bathtub or other water container.
12. Do not run cord under carpeting. Do not cover cord with throw rugs, runners or the like. Arrange cord away from traffic areas and where it will not be tripped over.
13. To disconnect this appliance, turn controls to the off position, then remove plug from outlet.
14. Connect to properly grounded outlets only.
15. This appliance, when installed, must be electrically grounded in accordance with local codes or, in the absence of local codes, with the current CSA C22.1 Canadian Electrical Code or for U.S.A. Installations, follow local codes and the National Electrical Code, ANSI/NFPA NO.70.
16. **There is a protective thermostat limiter inside the heater. When the inner temperature over heats, the thermostat limiter will shut off the power supply to avoid the risk of fire damage to the appliance.**
17. The heaters must not be located immediately below a socket-outlet.
18. Do not insert or allow foreign objects to enter any ventilation or exhaust opening as this may cause an electric shock or fire, or damage the appliance.
19. To prevent a possible fire, do not block air intakes or exhaust in any manner. Do not use on soft surfaces, like a bed, where opening may become blocked.
20. This appliance has hot and arcing or sparking parts inside. Do not use where gasoline, paint, or flammable liquids are used or stored. This fireplace should not be used as a drying rack for clothing. Christmas stockings or decorations should not be hung in the area of it.
21. Use this appliance only as described in the manual. Any other use not recommended by the manufacturer may cause fire, electric shock or injury to persons.
22. Always plug heaters directly into a wall outlet/receptacle. Never use with an extension cord or reloadable power tap (outlet/power strip).
23. See Figure 1 for the follow directions.
    This heater is for use on 120 volts. The cord has a plug as shown in figure 1.See Figure 1 for grounding instruction. An adapter as shown at C is available for connecting three-blade grounding type plugs to two-slot receptacles. The green grounding plug extending from the adapter must be connected to a permanent ground such as a properly grounded outlet box. The adapter should not be used if a three-slot grounded receptacle is available.

FIGURE 1



SAVE THESE INSTRUCTIONS

PARTS LIST

Part Name	FP-30-1
Ember bed	√
Heater/Blower Assembly	√
Thermostat	√
Knob for Heater Temperature control	√
Down light	√
Main PCBA	√
Control Panel Circuit Board	√
Flame Generator Drive Motor	√
Flame Generator/Spinner	√
Decorative Brick Panels	√
Remote Control-4 Buttons	√



Cold climate installation recommendation: When installing this unit against a Non-insulated exterior wall or chase, it is Mandatory that outer walls be insulated to Conform to applicable insulation codes.

ELECTRICAL SPECIFICATIONS

Voltage: 120 VAC, 60 Hz

Watts: 1400 Watts

ELECTRICAL CONNECTION

The unit comes standard with 6 feet (1.8m) three wire cord, exiting from the rear of the fireplace. Plan the installation to avoid the use of an extension cord. If an extension cord must be used, it must be a minimum 16 AWG; three wires with grounding type plug connection and rated not less than 1875 Watts The cord shall not be more than 20 feet (6m) in length.

CLEANING TRIM

Clean the metal trim using a soft cloth, slightly dampened with citrus oil based product and buff With a clean soft cloth. **DO NOT** use brass polish or household cleaners as these products will damage the metal trim. Citrus oil based products can be obtained at supermarkets or hardware stores

MAINTENANCE

The motors used on the fan and the flame generator assembly are pre-lubricated for extended bearing life and require no further lubrication. However, periodic cleaning/vacuuming of the fan/heater unit is recommended. Make sure the unit is turn OFF and unplugged whenever you are cleaning the heater or fireplace,

⚠ WARNING Make sure the power is turned off before proceeding. Any electrical repairs or rewiring of this unit should be carried out by a licensed electrician in accordance with national and local codes If repairing or replacing any electrical component or wiring, the original wire routing, color coding and securing locations must be followed.

⚠ WARNING Electric outlet wiring must comply with local building codes and other applicable regulations to reduce the risk of fire, electrical shock and injury to persons.

⚠ WARNING Do not use this fireplace if any part of it has been under water. Immediately call a qualified service technician to inspect the fireplace and replace any part of the electrical system.

⚠ WARNING Disconnect power before attempting any maintenance or cleaning to reduce the risk of fire, electrical shock or personal injury.

⚠ WARNING During any service of this appliance, the power to the unit must be turned off. First turn the main power switch to the "OFF" position. Then remove the electrical plugfrom the wall outlet.

OPERATING INSTRUCTIONS·CONTROL FUNCTION

CONTROL PANEL ACCESS

Control panel can be accessed at upper-right corner of appliance

OPERATION INSTRUCTIONS WITHOUT REMOTE

POWER

The POWER button turns the appliance on or off. It has a memory function; the button turns off all functions at once but retains the settings in the memory. By pressing the button again, the unit will turn on at the same settings. If the TIMER has been set & time has expired all functions will stop. Press the POWER button start the appliance.

FLAME

The FLAME control switch manages the flame brightness. There are 4 brightness levels and an off position. Each time the FLAME button is pressed, the intensity of the flame decreases. When adjusting the FLAME button, a number indicating the brightness of flame will be visible on the digital display. After turning on digital display, if nothing happens within 10 seconds, digital display will turn off. There is a down light over the ember bed. When the FLAME button is in the ON position, down light will turn on, it will turn off in OFF position..

The FLAME button has locking function. Press the FLAME button for 5 seconds. The down light will turn off. When the ember bed light flashes 6 times, it is confirming the flame function is locked. To remove locking function press FLAME button for 5 seconds, the ember bed light will flash 6 times, both the flame light and ember bed will be on.

HEATER

The HEATER button turns the heater on and off. When in ON position, press the HEATER button 5 seconds and enter temperature adjustment mode. In the adjustment mode, the digital indicator will flash at .05 second intervals. There are 23 temperature settings: 72℉—73℉—74℉…82℉—ON—OFF—62℉—63℉—64℉…71℉(22℃—23℃—24℃…27℃-ON—OFF—17℃—18℃…21℃). After the temperature is selected the digital indicator will flash 5 times and will exit from setting status. After turning on the digital temperature display, if nothing happens within 10 seconds, digital display will expire.

Temperature Switch Function: With the HEATER in the ON position, press the POWER button for 5 seconds, current temperature indicator will flash 3 times; after that it will switch to another temperature.

This button has a locking function. Press the HEATER button for 10 seconds, the ember bed light will flash 6 times, indicating that the HEATER function is locked. To remove locking the function press the HEATER button 10 seconds the ember bed light will flash 6 times, indicating the locking function has been removed. Press HEATER button again, and the heating function will resume.

TIMER

The TIMER has adjustable settings at 30 minute intervals. After turning on the digital display if nothing happens for 10 seconds the display will shut off. After the desired (set) time has expired the TIMER indicator light will flash 6 times and all functions will stop. All appliance settings EXCEPT the TIMER will be retained in the memory.

After entering the time setting press the power button to remove the setting function and retain in the memory.

OPERATION INSTRUCTIONS WITH REMOTE

POWER

The POWER button turns the appliance on and off.It has a memory function; the button turns off all functions at once but retains settings in the memory.

FLAME

The FLAME button manages the flame brightness. Each time the FLAME button is pressed the intensity of the flame decreases. There are four brightness levels you can cycle through including the OFF setting. When adjusting the FLAME button a number will appear on the digital display indicating the brightness of the flame. The FLAME button does not have a locking or unlocking function.

HEATER

The HEATER button turns the heater on and off. When pressing HEATER button on the remote, the default setting temperature is 72° F(22° C).The HEATER button does not have locking or remove locking function.

TIMER

The timer may be adjusted at 30 minute intervals. The temperature setting will be visible on the digital display.

NOTE: This equipment has been tested and found to comply with the limits for Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and the receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

ACAUTION This remote control uses 1 CR2032 lithium button cell battery (included). Never dispose of batteries in fire, except under conditions of controlled incineration. Failure to observe this precaution may result in an explosion.



This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

1) This device may not cause harmful interference.
2) This device must accept any interference received, including interference that may cause undesired operation.

Modifications not approved by the party responsible for compliance could void user's authority to operate the equipment.

This Class B digital apparatus complies with Canadian ICES-003.

TROUBLE SHOOTING GUIDE

MODELS: FP-30-1

PROBLEM	SOLUTION
1. No power or function.	1a.Check that unit is plugged into a standard 120V wall outlet. 1b.Press power button on the control panel.
2. Main power switch lights up, but no flame effect.	2a. Open the top and back panel to check if the flame spindle has fallen off from spindle motor.
3. Have flame effect, but heater does not blow warm air.	3a. Confirm temperature setting exceeds room temperature. 3b. Try to turn on/off HEATER button several times to make sure it is in the "ON" position.
4. Heater does not work, but Power and Heater switches are in the "ON" position and thermostat is set on "HI".	4a. Turn all switches to the "OFF" position and unplug the unit from the wall outlet for 5 minutes. After 5 minutes plug the unit back into wall outlet, and operate as normal.

1 YEAR LIMITED WARRANTY

Electric Fireplaces

BASIC WARRANTY

Whalen Electric Fireplace is free from manufacturing and material defects for a period of one year from date of purchase, subject to the following conditions and limitations

1. This electric fireplace must be installed and operated at all times in accordance with the installation and operating instructions furnished with the product. Any unauthorized repair, alteration, willful abuse, accident, or misuse of the product shall nullify this warranty.
2. This warranty is non-transferable, and is made to the original owner, provided that the purchase was made through an authorized supplier of the company.
3. The warranty is limited to the repair or replacement of part(s) found to be defective in material or workmanship, provided that such part(s) have been subjected to normal conditions of use and service, after said defect is confirmed by the Company's inspection.
4. The Company may, at its discretion, fully discharge all obligations with respect to this warranty by refunding the wholesale price of the defective part(s).
5. Any installation, labor, construction, transportation, or other related costs/expenses arising from defective part(s), repair, replacement, or otherwise of same, will not be covered by this warranty, nor shall the Company assume responsibility for same.
6. The owner/user assumes all other risks, if any, including the risk of any direct, indirect or consequential loss or damage arising out of the use, or inability to use the product, except as provided by law.
7. All other warranties - expressed of implied – with respect to the product, its components and accessories, or any obligations/liabilities on the part of the Company are hereby expressly excluded.
8. The Company neither assumes, nor authorizes any third party to assume, on its behalf, any other liabilities with respect to the sale of the Whalen product.
9. The warranties as outlined within this document do not apply to non Whalen accessories used in conjunction with the installation of this product. This warranty is void if:

a. The fireplace is subjected to prolonged periods of dampness or condensation.
b. Any unauthorized alteration, willful abuse, accident, or misuse of the product.
c. You do not have the original receipt of purchase.

IF WARRANTY SERVICE IS NEEDED

Contact the company, at parts@whalenfurniture.com Or call 00-1-866-942-5362. Make sure you have your warranty, your sales receipt, location of purchase and the model/serial number of your Whalen products.

For update and revisions to this manual
Please see our website
www.whalenstyle.com

Whalen Furniture Mfg ., Inc
Made in China
Printed in China

CHIMENEA ELÉCTRICA

CHIMENEA SIN RESPIRADERO CON CALENTADOR

MANUAL DE OPERACIÓN DEL PROPIETARIO

MODELO: FP- 30-1

NFORMACIÓN DE SEGURIDAD PARA EL CONSUMIDOR

LEA ESTE MANUAL ANTES DE INSTALAR Y OPERAR ESTE APARATO

⚠ ADVERTENCIA

EN CASO DE NO SEGUIR LA INFORMACIÓN EN ESTE MANUAL, UNA DESCARGA ELÉCTRICA O UN INCENDIO PUEDE PROVOCAR DAÑOS A LA PROPIEDAD, LESIONES PERSONALES O LA PÉRDIDA DE LA VIDA.

Gracias y felicitaciones por la adquisición de una chimenea Whalen. Lea las Instrucciones de Instalación antes de utilizar este aparato.

IMPORTANTE: Antes de comenzar la instalación, lea detenidamente todas las instrucciones y advertencias. El incumplimiento de estas instrucciones podría provocar una posible descarga eléctrica, riesgo de incendio, y/o lesiones y anulará la garantía.

Para el servicio a la clientela :

00-1-866-942-5362
Hora Estandar del Pacífico:8:30 am – 4:30 pm de Lunes a Viernes
O visite nuestra página de Internet 24 horas al día, 7 dias de la semana para ayuda en su producto
En: **www.whalenstyle.com**
O mande un correo eléctronico a **parts@whalenfurniture.com**

ATENCIÓN

Requiere también
de madera chimenea
Mantel

Whalen Furniture Mfg ., Inc
Hecho en China
Impreso en China

MANUAL DE INSTRUCCIONES

Al utilizar aparatos eléctricos, siempre deberán tomarse precauciones básicas para disminuir el riesgo de incendio, descarga eléctrica y/o lesiones, incluyendo lo siguiente:

1. Lea todas las instrucciones antes de usar este aparato
2. Este aparato se calienta cuando está en uso. Para evitar quemaduras, no permita que la piel sin protección toque superficies calientes. Si existen, utilice las asas al mover este aparato.
   ⚠ PELIGRO Bajo determinadas condiciones anormales, se pueden generar altas temperaturas. No cubra ni obstruya parcial ni completamente el frente del calentador.
   ⚠ ADVERTENCIA Para evitar sobrecalentamiento, no cubra el calentador. El mismo no puede utilizarse en un closet.
3. ⚠ PRECAUCIÓN El aparato no debe ser utilizado por niños ni por personas con capacidades físicas, sensoriales o mentales reducidas.
4. Se deben avisar a los niños que no jueguen con el calentador.
5. Desconecte siempre este aparato cuando no esté en uso.
6. No utilice ningún calentador con cables o enchufes dañados ni después de que el aparato haya tenido un mal funcionamiento, se haya caído o dañado de cualquier manera.
7. Si el cable de alimentación de corriente está dañado, debe ser reemplazado por el fabricante, su agente de servicio u otra persona con las mismas calificaciones para prevenir los accidentes.
8. Todas las reparaciones a esta chimenea deberán ser realizadas por una persona calificada de mantenimiento.
9. Bajo ninguna circunstancia deberá modificarse esta chimenea. Las piezas que se tengan que retirar para la reparación se deben reemplazar antes de poner a funcionar esta chimenea de nuevo.
10. No lo use en exteriores.
11. Este calentador no está diseñado para usarse en baños, áreas de lavado ni en lugares interiores similares. Nunca coloque este electrodoméstico en lugares donde se pueda caer dentro de una bañera u otro recipiente con agua.
12. No coloque el cable debajo de una alfombra. No cubra el cable con tapetes, alfombras de pasillo o cubiertas similares. Coloque el cable lejos de las zonas de tránsito, donde nadie se pueda tropezar y caer.
13. Para desconectar este aparato, coloque los controles en la posición de apagado, y luego retire el enchufe del tomacorriente.
14. Solamente conecte el aparato a tomacorrientes que estén debidamente conectados a tierra.
15. Al instalar este aparato, deberá tener una conexión eléctrica a tierra de acuerdo con los códigos locales o, en ausencia de códigos locales, con el Código de Electricidad Canadiense vigente norma CSA C22.1 o para las instalaciones en EE.UU., siga los códigos locales y el Código Nacional de Electricidad, ANSI/NFPA NO.70.
16. **El calentador tiene un termostato limitador en su interior. Cuando la temperatura interna sube demasiado o se produce un calentamiento anormal, el dispositivo de protección del termostato corta el suministro de energía para evitar que la chimenea se dañe o se produzca riesgo de incendio.**
17. Los calentadores no pueden colocarse inmediatamente debajo de un tomacorriente.
18. No inserte ni permita que entren objetos extraños a las aperturas de ventilación o de extracción, ya que esto puede ocasionar una descarga eléctrica, un incendio o puede dañar el calentador.
19. A fin de evitar un posible incendio, no bloquee las entradas ni las salidas de aire de manera alguna. No lo coloque sobre superficies suaves, como una cama, donde podrían bloquearse las aberturas.
20. Este aparato tiene piezas calientes y piezas que producen arcos eléctricos o chispas en su interior. No lo utilice en áreas donde se use o guarde gasolina, pintura u otros líquidos inflamables. Esta chimenea no debe utilizarse como un soporte para secar ropa. No deben colgarse medias para los regalos de Navidad ni elementos decorativos cerca del aparato.
21. Utilice este aparato únicamente como se describe en el manual. Cualquier otro uso no recomendado por el fabricante puede ocasionar incendio, descarga eléctrica o lesiones a personas.
22. Siempre enchufe los calentadores directamente en un receptáculo o tomacorriente de pared. Nunca lo use con una extensión o un contacto múltiple con tomas reubicables (tomacorriente/enchufe múltiple).
23. Vea la Figura 1 para consultar las indicaciones a seguir. Este calentador debe utilizarse con 120 voltios. El cable incluye un enchufe tal como se muestra en la Figura 1. Vea las instrucciones de conexión a tierra en la Figura 1. Hay un adaptador, como se ilustra en C, disponible para conectar enchufes de conexión a tierra de tres clavijas en receptáculos de dos ranuras. El enchufe verde de conexión a tierra que se extiende desde el adaptador debe conectarse a una toma de tierra permanente, como la de una caja de tomacorriente correctamente conectada a tierra. No es necesario utilizar el adaptador si hay un receptáculo de tres ranuras conectado a tierra.

FIGURA 1

GUARDE ESTAS INSTRUCCIONES

LISTA DE PIEZAS

Nombre de la Pieza	FP-30-1
Lecho de brasas	√
Conjunto de calentador/ventilador	√
Termostato	√
Perilla para el control de temperatura del calentador	√
abajo se enciende	√
PCBA (Conjunto de placa de circuito impreso) principal	√
Placa de circuitos del panel de control	√
Motor de accionamiento del generador de llama	√
Generador de llama/Disco giratorio	√
paneles de ladrillo decorativos	√
Mando a distancia-4 botones	√

Recomendación para la instalación en climas fríos:
Al instalar esta unidad contra un compartimiento o un pared exterior sin aislamiento, es obligatorio aislar las parèdes externas conforme con los códigos de aislamiento correspondientes

ESPECIFICACIONES ELÉCTRICAS
Voltaje: 120 VAC, 60 Hz
Vatios: 1400 Vatios

CONEXIÓN ELÉCTRICA

La unidad viene estándar con un cable trifilar de 6 pies (1,8 m) que sale de la parte trasera de la chimenea. Planifique la instalación para evitar el uso de un cable de extensión. Si fuera necesario usar un cable de extensión, éste deberá ser como mínimo No. 16 AWG; trifilar con conector de enchufe de conexión a tierra y clasificación no inferior a 1875 vatios. El cable no deberá tener más de 20 pies (6 m) de longitud

LIMPIEZA DE LA MOLDURA

Limpie la moldura metálica con un paño suave, ligeramente humedecido con un producto a base de aceite cítrico y púlalo con un paño suave y limpio. NO utilice productos de limpieza domésticos ni limpiametales, ya que estos productos dañarán la moldura metálica. Los productos a base de aceite cítrico pueden conseguirse en supermercados o ferreterías.

MANTENIMIENTO

Los motores que se utilizan en el ventilador y el conjunto generador de llama están prelubricados para prolongar la vida útil de los cojinetes y no es necesario lubricarlos más. Sin embargo, se recomienda limpiar/aspirar la unidad del ventilador/calentador. Asegúrese de que la unidad está **APAGADA** y **desenchufada** cuando esté limpiando el calentador o la chimenea

⚠ ADVERTENCIA Asegúrese de que la alimentación eléctrica esté desconectada antes de continuar. Toda reparación o renovación del sistema eléctrico de esta unidad deberá ser realizada por un electricista autorizado de acuerdo con códigos nacionales y locales. En caso de reparar o cambiar cualquier componente eléctrico, deberá seguirse la ruta de cables, el código de colores y los lugares de sujeción originales

⚠ ADVERTENCIA El cableado del tomacorriente eléctrico tiene que cumplir con los códigos de construcción locales y otras normas aplicables, a fin de reducir el riesgo de incendio, descarga eléctrica y lesiones a personas.

⚠ ADVERTENCIA No utilice esta chimenea si alguna de sus piezas ha estado sumergida en agua. Llame inmediatamente a un técnic de mantenimiento calificado para que inspeccione la chimenea y cambie cualquier pieza del sistema eléctrico.

⚠ ADVERTENCIA Desconecte la alimentación eléctrica antes de intentar realizar mantenimiento o limpieza para reducir el riesgo de incendio, descarga eléctrica o lesiones personales.

⚠ ADVERTENCIA Durante el mantenimiento de este aparato, deberá desconectarse la corriente a la unidad. Primero, coloque el interruptor de alimentación principal en la posición "APAGADO" ("OFF"). Luego, retire el enchufe eléctrico del tomacorriente de pared.

INSTRUCCIONES DE OPERACIÓN · FUNCIONES DE LOS

ACCESO AL PANEL DE CONTROL

Se puede tener acceso al panel de control por la esquina superior derecha del aparato.

INSTRUCCIONES DE OPERATION SIN CONTROL REMOTO

ENERGÍA

El botón de ENERGÍA enciende y apaga el aparato. El equipo tiene una función de memoria; el botón apaga todas las funciones a la vez, pero retiene los ajustes en la memoria. Al presionar el botón otra vez, la unidad se encenderá nuevamente con los mismos ajustes. Si se ha ajustado el TEMPORIZADOR y el tiempo se ha vencido, todas las funciones se detendrán. Presione el botón de ENERGÍA para encender el aparato.

LLAMA

El interruptor de control de la LLAMA controla la brillantez de la llama.Hay 4 niveles de brillantez y una posición de apagado. Cada vez que se presiona el botón LLAMA, la intensidad de la llama disminuye. Al ajustar el botón LLAMA, aparecerá en la pantalla digital un número indicando el grado de brillantez de la llama.Después de encender la pantalla digital,si no sucede nada en 10 segundos, se apagará la pantalla digital. Hay una luz hacia abajo que ilumina el lecho de brasas.Cuando el botón LLAMA se coloca en la posición ENCENDIDO,se encenderá la luz de emisión hacia abajo,y se apagará en la posición APAGADO.
El botón de la LLAMA también tiene una función de bloqueo. Presione el botón LLAMA durante 5 segundos. La luz de emisión hacia abajo se apagará. Cuando la luz del lecho de brasas destelle 6 veces, está confirmando que la función de llama está bloqueada.
Para quitar la función de bloqueo, presione el botón LLAMA durante 5 segundos, la luz del lecho de brasas destellará 6 veces, indicándole que la luz de llama y del lecho de brasas se encenderán

CALENTADOR

El botón del CALENTADOR enciende y apaga el calentador. Cuando está en la posición ENCENDIDO, presione el botón del CALENTADOR 5 segundos y seleccione la modalidad de ajuste de temperatura. En la modalidad de ajuste,el indicador digital destellará a intervalos de 0.05 segundos.Hay 23 ajustes temperatura: 72℉－73℉－74℉…82℉—ENCENDIDO—APAGADO—62℉—63℉－64℉…71℉(22℃－23℃－24℃…27℃- ENCENDIDO—APAGADO—17℃－18℃…21℃). Una vez que haya seleccionado la temperatura, el indicador digital destellará 5 veces y saldrá de la modalidad de ajuste. Después de encender la pantalla digital de temperatura, si no sucede nada en 10 segundos, se apagará la pantalla digital.
Función de cambio de temperatura: Con el CALENTADOR colocado en la posición ENCENDIDO, presione el botón de ENERGÍA durante 5 segundos, el indicador de la temperatura actual destellará 3 veces; después de lo cual cambiará a otra temperatura.
Este botón tiene una función de bloqueo. Presione el botón CALENTADOR durante 10 segundos, la luz del lecho de brasas destellará 6 veces, indicando que la función de CALENTADOR está bloqueada. Para quitar la función de bloqueo, presione el botón CALENTADOR 10 segundos y la luz del lecho de brasas destellará 6 veces, indicándole que se ha quitado la función de bloqueo. Presione nuevamente el botón CALENTADOR, y la función de calentamiento continuará funcionando.

TIMER

IEl TEMPORIZADOR tiene ajustes que se pueden regular a intervalos de 30 minutos. Después de encender la pantalla digital, si no sucede nada en10 segundos, se apagará la pantalla digital. Después que haya terminado el tiempo deseado (ajustado), la luz indicadora del TEMPORIZADOR destellará 6 veces y todas las funciones se detendrán. Todos los ajustes del aparato EXCEPTO el TEMPORIZADOR se mantendrán en la memoria.
Después de poner el tiempo deseado, presione el botón de energía para salir de la función de ajuste y mantener el tiempo en la memoria.

INSTRUCCIONES DE OPERACIÓN CON CONTROL REMOTO

ENERGÍA

El botón de ENERGÍA enciende y apaga el aparato. El equipo tiene una función de memoria; el botón apaga todas las funciones a la vez, pero retiene los ajustes en la memoria.

FLAME

El botón de LLAMA controla la brillantez de la llama. Cada vez que se presiona el botón LLAMA, la intensidad de la llama disminuye. Hay cuatro niveles de brillantez que usted puede utilizar incluso la opción de APAGADO. Al ajustar el botón LLAMA, aparecerá en la pantalla digital un número indicando el grado de brillantez de la llama. El botón LLAMA no tiene una función de bloqueo o desbloqueo.

HEATER

El botón CALENTADOR enciende y apaga el calentador. Al presionar el botón CALENTADOR en el control remoto, la temperatura predeterminada de fábrica es 72°F (22°C). El botón CALENTADOR no tiene una función de bloqueo o desbloqueo.

TIMER

El temporizador puede ajustarse a intervalos de 30 minutos. El ajuste de temperatura aparecerá en la pantalla digital.

NOTA: Este equipo ha sido probado, determinándose que cumple con los límites establecidos para un dispositivo digital de clase B, de acuerdo con la Parte 15 de las Normas de la FCC. Estos límites han sido diseñados para brindar una protección razonable contra la interferencia dañina en una instalación residencial. **Este equipo genera, utiliza, y puede irradiar energía de radiofrecuencia y, en caso de no ser instalado y utilizado de acuerdo con las instrucciones, puede causar interferencias dañinas a la recepción de radio y televisión, lo cual se puede determinar apagando y encendiendo el equipo. Le recomendamos al usuario que intente corregir la interferencia con una o más de las siguientes medidas:**

- Reorientar o reubicar la antena receptora.
- Aumentar la distancia entre el equipo y el receptor.
- Conectar el equipo a un tomacorriente en un circuito diferente al que el receptor está conectado.
- Consultar al distribuidor o algún técnico de radio/TV con experiencia.

⚠PRECAUCIÓN Este control remoto utiliza 1 batería CR2032 de lones de litio tipo botón (incluida). Nunca deseche las baterías en el fuego, excepto en condiciones de incineración controlada. SI no se obedece esta precaución, podría producirse una explosión



Este dispositivo cumple con lo dispuesto en la Parte 15 de las Normas de la Comisión Federal de Comunicaciones (FCC por sus siglas en inglés). Su funcionamiento se encuentra sujeto a las dos condiciones siguientes:

1) Este dispositivo no puede ocasionar interferencia dañina.
2) Este dispositivo debe aceptar cualquier interferencia recibida, incluyendo la interferencia que pueda ocasionar un funcionamiento indeseable.

Las modificaciones que no estén aprobados por la parte responsable de su aceptación podrían anular el derecho del usuario para operar el equipo.Este aparato digital de Clase B cumple con la norma canadiense ICES-003.

GUÍA DE LOCALIZACIÓN Y SOLUCIÓN DE PROBLEMAS

MODELOS: FP-30-1

PROBLEMA	SOLUCIÓN
1. No hay energía o no funciona.	1a.Compruebe que la unidad esté enchufada a un tomacorriente estándar de 120V. 1b.Presione el botón de energía en el panel de control.
2. Los interruptores principales se encienden, pero no hay efecto de llama.	2a. Abra el panel superior y trasero para comprobar si el husillo de la llama se ha zafado del motor de husillo.
3. El efecto de llama funciona, pero el calentador no echa aire caliente.	3a. Asegúrese de que el ajuste de temperatura sea superior a la temperatura ambiente. 3b. Trate de encender y apagar el botón CALENTADOR varias veces para asegurarse de que esté en la posición 'ENCENDIDO".
4. El calentador no funciona, pero los interruptores Energía (Power) y Calentador (Heater) están en la posición "ENCENDIDO" ("ON") y el termostato está ajustado en "ALTA" ("HI").	4a. Coloque todos los interruptores en la posición "APAGADO" ("OFF") y desenchufe la unidad del tomacorriente de la pared durante 5 minutos. Luego de 5 minutos, enchufe nuevamente la unidad al tomacorriente de la pared, y opérela de la manera habitual.

GARANTÍA LIMITADA DE 1 AÑO

Chimeneas Eléctricas

GARANTÍA BÁSICA

La Chimenea Eléctrica Whalen está libre de defectos de fabricación y materiales, durante un período de un año a partir de la fecha de compra, sujeto a las siguientes condiciones y limitaciones.

1. Esta chimenea eléctrica tiene que instalarse y operarse en todo momento de acuerdo con las instrucciones de instalación y funcionamiento suministradas con el producto. Toda reparación, alteración, maltrato intencionado, accidente, o mala utilización del producto que no esté autorizada anulará esta garantía.
2. Esta garantía no es transferible y se otorga al propietario original, siempre y cuando la compra se haya realizado a través de un proveedor autorizado de la compañía.
3. La garantía está limitada a la reparación o el reemplazo de piezas que se hayan encontrado defectuosas en relación con la mano de obra o el material, siempre y cuando estas piezas hayan sido sometidas a condiciones normales de uso y mantenimiento, luego de que dicho defecto haya sido confirmado por la inspección de la Compañía.
4. Según su criterio, la Compañía podrá cumplir con todas las obligaciones con respecto a esta garantía al reembolsar el precio mayorista de las piezas defectuosas.
5. ATodos los costos de instalación, mano de obra, construcción, transporte u otros gastos que surjan de las piezas defectuosas, la reparación, el reemplazo, o similares no estarán cubiertos por esta garantía, ni la Compañía asumirá la responsabilidad de éstos.
6. El propietario/usuario asume todos los demás riesgos, si los hay, que incluyen el riesgo de cualquier pérdida o daño directo, indirecto o resultante que surja del uso o la incapacidad para usar el producto, a excepción de lo dispuesto por ley.
7. Por la presente se excluyen expresamente todas las otras garantías, ya sean explícitas o implícitas, con respecto al producto, sus componentes y accesorios, o cualquier obligación/responsabilidad por parte de la Compañía.
8. La Compañía no asume, ni autoriza a ningún tercero a asumir en su nombre, ninguna otra responsabilidad con respecto a la venta del producto Whalen.
9. Las garantías tal como se describen en este documento no se aplican a accesorios que no sean de Whalen que se utilicen en conjunto con la instalación de este producto. Esta garantía no tendrá validez si:
   a. La chimenea es sometida a períodos prolongados de humedad o condensación.
   b. Toda alteración, maltrato intencionado, accidente, o mala utilización del producto que no esté autorizada.
   c. Usted no tiene el recibo original de compra.

SI NECESITA EL SERVICIO DE LA

Asegúrese de tener la garantía, el recibo de venta, el lugar de la compra y el número de modelo/serie de su Chimenea Whalen.

Whalen Furnirure Mfg ., Inc
Hecho en China
Impreso en China

ATTACHMENT C

23”insert

This is the prototype sample of the 23”insert with the control panel/buttons on the right side. We will move to the left side at same location as what we did on the 30”insert, same button shape and icons.

26”insert

This is the 2011 version we shipped

This is the prototype sample of the 2012 version with NEW log.
We will move the control panel to the left side, with same button shape and icons as the 30”insert.

30”insert





This is the 30”insert we are moving forward with the control panel in the left side, button shape and Icons as above picture.
We will do the same control panel location, shape and Icons to the 23”and 26”insert.



ATTACHMENT D

UNITED STATES INTERNATIONAL TRADE COMMISSION
Washington, D.C.

Before The Honorable David P. Shaw
Administrative Law Judge

In the Matter of

CERTAIN ELECTRIC FIREPLACES, COMPONENTS THEREOF, MANUALS FOR SAME, CERTAIN PROCESSES FOR MANUFACTURING OR RELATING TO SAME AND CERTAIN PRODUCTS CONTAINING SAME

Inv. No. 337-TA-791/826

PROPOSED CONSENT ORDER

The United States International Trade Commission ("Commission") has instituted the above captioned investigation (the "Investigation") under Section 337 of the Tariff Act of 1930 as amended (19 U.S.C. § 1337), based upon the allegations in the Complaint filed by Twin-Star International Inc. and TS Investment Holding Corp. ("Complainants"), which alleged unfair acts in the importation into the United States, the sale for importation, and the sale within the United States after importation, of certain electric fireplaces, components thereof, manuals for same, certain processes for manufacturing or relating to same and certain products containing same ("Subject Electric Fireplaces") by, among others, Respondent Whalen Furniture Manufacturing Inc. ("Whalen").

Whalen has executed a Consent Order Stipulation in which it agrees to the entry of this Consent Order and to all waivers and other provisions as required by the Commission's Rules of Practice and Procedure, and has filed a Motion for Termination of the Investigation with respect

to Whalen based on the Consent Order Stipulation. In particular, Whalen has stipulated as follows:

A. Respondent Whalen is a company organized and existing under the laws of the state of California, with its principal place of business at 1578 Air Wing Road, San Diego, California 92154.

B. The Commission has *in rem* jurisdiction over the Subject Electric Fireplaces which are the subject of this Investigation and the Commission has *in personam* jurisdiction over Whalen for the purposes of this Stipulation and Consent Order.

C. Whalen stipulates that it shall not sell for importation, import into the United States, or sell in the United States after importation, or knowingly aid, abet, encourage, participate in, or induce the sale for importation, importation into the United States, or sale in the United States, alone or incorporated with furniture items or other products, (i) any electric fireplace inserts as shown in Attachment A, or manufactured, either directly or indirectly, by Respondent Reliap Industrial Co. ("Reliap") and/or Jason Yue or any entity directly or indirectly associated with Reliap and/or Jason Yue, or that infringe U.S. Copyright Registration No. VA0001772669 or U.S. Copyright Registration No. VA0001772661, or are produced using or which contain misappropriated Twin Star trade secrets; and (ii) any manuals which infringe upon U.S. Copyright Registration No. TX007350474 or U.S. Copyright Registration No. TX0007350476, or any manuals as shown in Attachment B, except under consent or license from the Complainants, their successors, or assigns for a period of time ending five (5) years from the date of the Settlement Agreement attached as

Exhibit 3 to the Joint Motion For Termination. Whalen agrees that it cannot promote, sell, market, use and import (or cause to be imported) electric fireplace inserts, alone or incorporated with furniture items or other products, for a period of one (1) year from the date of the Settlement Agreement attached as Exhibit 3 to the Joint Motion to Terminate, except for the electric fireplace inserts embodying at least all of the characteristics as shown in Attachment C, as well as additional models that embody a curved glass front as part of the facade.

D. Whalen expressly waives all rights to seek judicial review or otherwise challenge or contest the validity of the Consent Order.

E. Whalen will cooperate with and will not seek to impede by litigation or other means the Commission's efforts to gather information under subpart 1 of the Commission's Rules of Practice and Procedure, 19 C.F.R. §210.

F. Enforcement, modification, or revocation of the Consent Order will be carried out pursuant to subpart I of the Commission's Rules of Practice and Procedure, 19 C.F.R. §210.

G. The Consent Order shall not apply with respect to any claim of any intellectual property right that has expired or been found or adjudicated invalid or unenforceable by the Commission or a court or agency of competent jurisdiction, provided that such finding or judgment has become final and nonreviewable.

H. Whalen will not seek to challenge the validity or enforceability of the intellectual property rights set forth in the Complaint for Inv. No. 337-TA-826 – *i.e.*, U.S. Copyright Registration Nos. VA0001772661, VA0001772669, TX007350474, TX0007350476 and Complainants' asserted trade secrets (the "Subject

Intellectual Property") – in any administrative or judicial proceeding to enforce the Consent Order.

I. Whalen understands and acknowledges that with regard to the information it has provided in the course of discovery in the Investigation, including but not limited to documents, interrogatory responses, and transcripts of sworn deposition testimony, Complainants may seek to introduce such information as evidence in the Investigation after Whalen has been terminated as a respondent. Whalen hereby waives its right to object to, to rebut, or to otherwise address the introduction of such information into the record of the Investigation.

J. Whalen understands and acknowledges that if the Commission enters this Consent Order, Whalen will have waived its right to introduce evidence, cross-examine witnesses, and otherwise participate in the Investigation in any fashion.

K. The signing of this Stipulation and Proposed Consent Order is for settlement purposes only and does not constitute an admission by Whalen that an unfair act has been committed.

L. Other than the Settlement Agreement attached as Exhibit 3 to the Joint Motion to Terminate, there are no agreements, written or oral, express or implied, between Whalen and Complainants concerning the subject matter of the Investigation.

NOW, THEREFORE, the Commission issues the following Consent Order:

1. Upon entry of this Consent Order, Whalen shall not sell for importation, import into the United States, or sell in the United States after importation, or knowingly aid, abet, encourage, participate in, or induce the sale for importation, importation into the United States, or sale in the United States, alone or incorporated with

furniture items or other products, any electric fireplace inserts as shown in Attachment A, or manufactured, either directly or indirectly, by Respondent Reliap Industrial Co. ("Reliap") and/or Jason Yue or any entity directly or indirectly associated with Reliap and/or Jason Yue, or that infringe U.S. Copyright Registration No. VA0001772669 or U.S. Copyright Registration No. VA0001772661, or are produced using or which contain misappropriated Twin Star trade secrets; and (ii) any manuals which infringe upon U.S. Copyright Registration No. TX007350474 or U.S. Copyright Registration No. TX0007350476, or any manuals as shown in Attachment B, except under consent or license from the Complainants, their successors, or assigns for a period of time ending five (5) years from the date of the Settlement Agreement attached as Exhibit 3 to the Joint Motion. Further, Whalen cannot promote, sell, market, use and import (or cause to be imported) electric fireplace inserts, alone or incorporated with furniture items or other products, for a period of one (1) year from the date of the Settlement Agreement attached as Exhibit 3 to the Joint Motion, except for the electric fireplace inserts embodying at least all of the characteristics as shown in Attachment C, as well as additional models that embody a curved glass front as part of the facade.

2. Whalen shall be precluded from seeking judicial review or otherwise challenging or contesting the validity of this Consent Order.

3. Whalen shall cooperate with and shall not seek to impede by litigation or other means the Commission's efforts to gather information under subpart I of the Commission's Rules of Practice and Procedure, 19 C.F.R. §210.

4. Whalen shall not seek to challenge the validity or enforceability of the claims of the Subject Intellectual Property in any administrative or judicial proceeding to enforce the Consent Order.

5. If any of the Subject Intellectual Property expires or is held invalid or unenforceable by a court or agency of competent jurisdiction, provided that such finding is final and non-reviewable, this Order shall become null and void.

6. The Investigation is hereby terminated with respect to Whalen, and Whalen is hereby dismissed as a named respondent in the Investigation; provided, however, that enforcement, modification, or revocation of this Consent Order shall be carried out pursuant to Subpart I of the Commission's Rules of Practice and Procedures, 19 C.F.R. §210.

BY ORDER OF THE COMMISSION:

James R. Holbein

Secretary to the Commission

EXHIBIT 2

UNITED STATES INTERNATIONAL TRADE COMMISSION
Washington, D.C.

Before The Honorable David P. Shaw
Administrative Law Judge

In the Matter of

CERTAIN ELECTRIC FIREPLACES, COMPONENTS THEREOF, MANUALS FOR SAME, CERTAIN PROCESSES FOR MANUFACTURING OR RELATING TO SAME AND CERTAIN PRODUCTS CONTAINING SAME

Inv. No. 337-TA-791/826

PROPOSED CONSENT ORDER

The United States International Trade Commission ("Commission") has instituted the above captioned investigation (the "Investigation") under Section 337 of the Tariff Act of 1930 as amended (19 U.S.C. § 1337), based upon the allegations in the Complaint filed by Twin-Star International Inc. and TS Investment Holding Corp. ("Complainants"), which alleged unfair acts in the importation into the United States, the sale for importation, and the sale within the United States after importation, of certain electric fireplaces, components thereof, manuals for same, certain processes for manufacturing or relating to same and certain products containing same ("Subject Electric Fireplaces") by, among others, Respondent Whalen Furniture Manufacturing Inc. ("Whalen").

Whalen has executed a Consent Order Stipulation in which it agrees to the entry of this Consent Order and to all waivers and other provisions as required by the Commission's Rules of Practice and Procedure, and has filed a Motion for Termination of the Investigation with respect

to Whalen based on the Consent Order Stipulation. In particular, Whalen has stipulated as follows:

A. Respondent Whalen is a company organized and existing under the laws of the state of California, with its principal place of business at 1578 Air Wing Road, San Diego, California 92154.

B. The Commission has *in rem* jurisdiction over the Subject Electric Fireplaces which are the subject of this Investigation and the Commission has *in personam* jurisdiction over Whalen for the purposes of this Stipulation and Consent Order.

C. Whalen stipulates that it shall not sell for importation, import into the United States, or sell in the United States after importation, or knowingly aid, abet, encourage, participate in, or induce the sale for importation, importation into the United States, or sale in the United States, alone or incorporated with furniture items or other products, (i) any electric fireplace inserts as shown in Attachment A, or manufactured, either directly or indirectly, by Respondent Reliap Industrial Co. ("Reliap") and/or Jason Yue or any entity directly or indirectly associated with Reliap and/or Jason Yue, or that infringe U.S. Copyright Registration No. VA0001772669 or U.S. Copyright Registration No. VA0001772661, or are produced using or which contain misappropriated Twin Star trade secrets; and (ii) any manuals which infringe upon U.S. Copyright Registration No. TX007350474 or U.S. Copyright Registration No. TX0007350476, or any manuals as shown in Attachment B, except under consent or license from the Complainants, their successors, or assigns for a period of time ending five (5) years from the date of the Settlement Agreement attached as

Exhibit 3 to the Joint Motion For Termination. Whalen agrees that it cannot promote, sell, market, use and import (or cause to be imported) electric fireplace inserts, alone or incorporated with furniture items or other products, for a period of one (1) year from the date of the Settlement Agreement attached as Exhibit 3 to the Joint Motion to Terminate, except for the electric fireplace inserts embodying at least all of the characteristics as shown in Attachment C, as well as additional models that embody a curved glass front as part of the facade.

D. Whalen expressly waives all rights to seek judicial review or otherwise challenge or contest the validity of the Consent Order.

E. Whalen will cooperate with and will not seek to impede by litigation or other means the Commission's efforts to gather information under subpart 1 of the Commission's Rules of Practice and Procedure, 19 C.F.R. §210.

F. Enforcement, modification, or revocation of the Consent Order will be carried out pursuant to subpart I of the Commission's Rules of Practice and Procedure, 19 C.F.R. §210.

G. The Consent Order shall not apply with respect to any claim of any intellectual property right that has expired or been found or adjudicated invalid or unenforceable by the Commission or a court or agency of competent jurisdiction, provided that such finding or judgment has become final and nonreviewable.

H. Whalen will not seek to challenge the validity or enforceability of the intellectual property rights set forth in the Complaint for Inv. No. 337-TA-826 – *i.e.*, U.S. Copyright Registration Nos. VA0001772661, VA0001772669, TX007350474, TX0007350476 and Complainants' asserted trade secrets (the "Subject

Intellectual Property") – in any administrative or judicial proceeding to enforce the Consent Order.

I. Whalen understands and acknowledges that with regard to the information it has provided in the course of discovery in the Investigation, including but not limited to documents, interrogatory responses, and transcripts of sworn deposition testimony, Complainants may seek to introduce such information as evidence in the Investigation after Whalen has been terminated as a respondent. Whalen hereby waives its right to object to, to rebut, or to otherwise address the introduction of such information into the record of the Investigation.

J. Whalen understands and acknowledges that if the Commission enters this Consent Order, Whalen will have waived its right to introduce evidence, cross-examine witnesses, and otherwise participate in the Investigation in any fashion.

K. The signing of this Stipulation and Proposed Consent Order is for settlement purposes only and does not constitute an admission by Whalen that an unfair act has been committed.

L. Other than the Settlement Agreement attached as Exhibit 3 to the Joint Motion to Terminate, there are no agreements, written or oral, express or implied, between Whalen and Complainants concerning the subject matter of the Investigation.

NOW, THEREFORE, the Commission issues the following Consent Order:

1. Upon entry of this Consent Order, Whalen shall not sell for importation, import into the United States, or sell in the United States after importation, or knowingly aid, abet, encourage, participate in, or induce the sale for importation, importation into the United States, or sale in the United States, alone or incorporated with

furniture items or other products, any electric fireplace inserts as shown in Attachment A, or manufactured, either directly or indirectly, by Respondent Reliap Industrial Co. ("Reliap") and/or Jason Yue or any entity directly or indirectly associated with Reliap and/or Jason Yue, or that infringe U.S. Copyright Registration No. VA0001772669 or U.S. Copyright Registration No. VA0001772661, or are produced using or which contain misappropriated Twin Star trade secrets; and (ii) any manuals which infringe upon U.S. Copyright Registration No. TX007350474 or U.S. Copyright Registration No. TX0007350476, or any manuals as shown in Attachment B, except under consent or license from the Complainants, their successors, or assigns for a period of time ending five (5) years from the date of the Settlement Agreement attached as Exhibit 3 to the Joint Motion. Further, Whalen cannot promote, sell, market, use and import (or cause to be imported) electric fireplace inserts, alone or incorporated with furniture items or other products, for a period of one (1) year from the date of the Settlement Agreement attached as Exhibit 3 to the Joint Motion, except for the electric fireplace inserts embodying at least all of the characteristics as shown in Attachment C, as well as additional models that embody a curved glass front as part of the facade.

2. Whalen shall be precluded from seeking judicial review or otherwise challenging or contesting the validity of this Consent Order.

3. Whalen shall cooperate with and shall not seek to impede by litigation or other means the Commission's efforts to gather information under subpart I of the Commission's Rules of Practice and Procedure, 19 C.F.R. §210.

4. Whalen shall not seek to challenge the validity or enforceability of the claims of the Subject Intellectual Property in any administrative or judicial proceeding to enforce the Consent Order.

5. If any of the Subject Intellectual Property expires or is held invalid or unenforceable by a court or agency of competent jurisdiction, provided that such finding is final and non-reviewable, this Order shall become null and void.

6. The Investigation is hereby terminated with respect to Whalen, and Whalen is hereby dismissed as a named respondent in the Investigation; provided, however, that enforcement, modification, or revocation of this Consent Order shall be carried out pursuant to Subpart I of the Commission's Rules of Practice and Procedures, 19 C.F.R. §210.

BY ORDER OF THE COMMISSION:

James R. Holbein

Secretary to the Commission

ATTACHMENT A

RELIAP

THE MOST RELIABLE FIREPLACE AROUND THE WORLD

23"—Electric Fireplace

Model No.: NW01E

Dimensions: 23.7"W×20"H×8.2"D

Options: Different front decorative trim



REAR DIRECTION MOUNTING

FRONT DIRECTION MOUNTING

FEATURE:

- Can be plugged directly into a standard 120V 60Hz outlet, 1400 Watts
- cUL listed
- 4600BTU, heat up 400 square feet room
- 5000 Hours life time LED light source
- Super infra red remote control
- The most quiet fireplace in industry
- Automatic room temperature control
- Flame brightness adjustable
- Flame and emberbed glow can be on seperately
- Can enjoy the flame effect without heat
- Can install with different front decorative trim
- The most reliable components in industry
- The most realistic flame effect

WDP01285

Copyright©Shenzhen Reliap Industrial Co.,Ltd

Tel:+86 755 29415053 Fax:+86 755 29683019
Website:www.reliap.com

RELIAP

THE MOST RELIABLE FIREPLACE AROUND THE WORLD

23" – Electric Fireplace

Model No: NW02E

Dimensions: 23.7"W×20"H×8.3"D

Options: Different front decorative trim



REAR DIRECTION MOUNTING

FRONT DIRECTION MOUNTING

FEATURE:

- Can be plugged directly into a standard 120V 60Hz outlet, 1400 Watts
- cUL listed
- 4600BTU, heat up 400 square feet room
- 50000 Hours life time LED light source
- Super infra red remote control
- The most quiet fireplace in industry
- Automatic room temperature control
- Flame brightness adjustable
- Flame and emberbed glow can be on seperately
- Can enjoy the flame effect without heat
- Can install with different front decorative trim
- The most reliable components in industry
- The most realistic flame effect

WDP01287

Copyright©Shenzhen Reliap Industrial Co.,Ltd

Tel:+86 755 29410052 Fax:+86 755 29683019
Website:www.reliap.com

RELIAP

THE MOST RELIABLE FIREPLACE AROUND THE WORLD

NW02F ELECTRIC FIREPLACE

Model No.: NW02F

Dimensions: 27"W×22.1"×9.5"D

Opetions: Different front decorative trim



REAR DIRECTION MOUNTING

FRONT DIRECTION MOUNTING

FEATURE

- Can be plugged directly into a standard 120V 60Hz outlet, 1400 Watts
- cUL listed
- 4600BTU, heat up 400 square feet room
- 5000 Hours life time LED light source
- Super infra red remote control
- The most quiet fireplace in industry
- Automatic room temperature control
- Flame brightness adjustable
- Flame and emberbed glow can be on seperately
- Can enjoy the flame effect without heat
- Can install with different front decorative trim
- The most reliable components in industry
- The most realistic flame effect

WDP01288

Copyright©Shenzhen Reliap Industrial Co.,Ltd

Tel:+86 755 29416054 Fax:+86 755 29833016
Website:www.reliap.com

RELIAP

THE MOST RELIABLE FIREPLACE AROUND THE WORLD

30 "ELECTRIC FIREPLACE

MODEL No: NW02H

Dimensions: 31"W× 24"H×9.5"D

Options: Different front decorative trim



REAR DIRECTION MOUNTING

FRONT DIRECTION MOUNTING

FEATURE:

- Can be plugged directly into a standard 120V 60Hz outlet, 1400 Watts
- cUL listed
- 4600BTU, heat up 400 square feet room
- 50000 Hours life time LED light source
- Super infra red remote control
- The most quiet fireplace in industry
- Automatic room temperature control
- Flame brightness adjustable
- Flame and emberbed glow can be on seperately
- Can enjoy the flame effect without heat
- Can install with different front decorative trim
- The most reliable components in industry
- The most realistic flame effect

WDP01289

Copyright©Shenzhen Reliap Industrial Co.,Ltd

Tel:+86 755 29419053 Fax:+86 755 29693019
Website:www.reliap.com

RELIAP

THE MOST RELIABLE FIREPLACE AROUND THE WORLD

NW22F ELECTRIC FIREPLACE

Model No.: NW22F

Dimensions: 27"W×17.6"H×9.5"D

Options: Different front decorative trim



REAR DIRECTION MOUNTING

FRONT DIRECTION MOUNTING



FEATURE

- Can be plugged directly into a standard 120V 60Hz outlet, 1400 Watts
- cUL listed
- 4600BTU, heat up 400 square feet room
- 50000 Hours life time LED light source
- Super infra red remote control
- The most quiet fireplace in industry
- Automatic room temperature control
- Flame brightness adjustable
- Flame and emberbed glow can be on seperately
- Can enjoy the flame effect without heat
- Can install with different front decorative trim
- The most reliable components in industry
- The most realistic flame effect

WDP01290

Copyright©Shenzhen ReliAp Industrial Co.,Ltd

Tel:+86 755 29416054 Fax:+86 755 29685019
Web site:www.reliap.com


19”
1.38”
18”
WDP01286
18”
7”

ATTACHMENT B

ELECTRIC FIREPLACE

VENT FREE FIREPLACE WITH HEATER

HOMEOWNERS OPERATING MANUAL

MODELS: FP-30-1 / FP-26-1 / FP- 26-2
FP-23-1 / FP-18-1

CONSUMER SAFETY INFORMATION

PLEASE READ THIS MANUAL BEFORE

INSTALLING AND OPERATING THIS APPLIANCE

⚠ WARNING

IF THE INFORMATION IN THIS MANUAL IS NOT FOLLOWED,

AN ELECTRIC SHOCK OR FIRE MAY RESULT IN PROPERTY DAMAGE,

PERSONAL INJURY, OR LOSS OF LIFE.

Thank you and congratulations on your purchase of a Whalen fireplace. Please read the Installation Instructions before using this appliance.

IMPORTANT: Read all instructions and warnings carefully before starting installation. Failure to follow these instructions may result in a possible electric shock, fire hazard, and/or injury and will void the warranty.

For Customer Service:

1-866-942-5362
Pacific Standard Time:8:30 a.m.-4:30 p.m.,Monday - Friday
Or visit our web site 24 hours a day,7 days a week for product assistance at
www.whalenfurniture.com
Or e-mail your request to **parts@whalenfurniture.com**

Whalen Furniture Mfg ., Inc
Made in China
Printed in China

INSTRUCTION MANUAL

When using electrical appliances, basic precautions should always be followed to reduce the risk or fire, electrical shock, and/or injury including the following:

1. Read all instructions before using this appliance.
2. This appliance is hot when in use. To avoid burns, do not let bare skin touch hot surfaces. If provided, use handles when moving this appliance.
   ⚠ DANGER High temperatures may be generated under certain abnormal conditions. Do not partially or fully cover or obstruct the front of the heater.
   ⚠ WARNING In order to avoid overheating, do not cover the heater. It cannot be used in a closet.
3. **⚠ CAUTION** The appliance should not be used by children or persons with reduced physical, sensory or mental capabilities.
4. Children should be advised not to play with the appliance.
5. Always unplug this appliance when not in use.
6. Do not operate any heater with a damaged cord or plug or after the appliance malfunctions, or if it has been dropped or damaged in any manner.
7. If the supply cord is damaged, it must be replaced by the manufacturer, it's service agent or similarly qualified persons in order to avoid a hazard.
8. Any repairs to this fireplace should be carried out by a qualified service person.
9. Under no circumstances should this fireplace be modified. Parts having to be removed for servicing must be replaced prior to operating this fireplace again.
10. Do not use outdoors.
11. This heater is not intended for use in bathrooms, laundry areas and similar indoor locations. Never locate this appliance where it may fall into a bathtub or other water container.
12. Do not run cord under carpeting. Do not cover cord with throw rugs, runners or the like. Arrange cord away from traffic areas and where it will not be tripped over.
13. To disconnect this appliance, turn controls to the off position, then remove plug from outlet.
14. Connect to properly grounded outlets only.
15. This appliance, when installed, must be electrically grounded in accordance with local codes or, in the absence of local codes, with the current CSA C22.1 Canadian Electrical Code or for U.S.A. Installations, follow local codes and the National Electrical Code, ANSI/NFPA NO 70.
16. **There is a protective thermostat limiter inside the heater. When the inner temperature over heats, the thermostat limiter will shut off the power supply to avoid the risk of fire damage to the appliance.**
17. The heaters must not be located immediately below a socket-outlet.
18. Do not insert or allow foreign objects to enter any ventilation or exhaust opening as this may cause an electric shock or fire, or damage the appliance.
19. To prevent a possible fire, do not block air intakes or exhaust in any manner. Do not use on soft surfaces, like a bed, where opening may become blocked.
20. This appliance has hot and arcing or sparking parts inside. Do not use where gasoline, paint, or flammable liquids are used or stored. This fireplace should not be used as a drying rack for clothing. Christmas stockings or decorations should not be hung in the area of it.
21. Use this appliance only as described in the manual. Any other use not recommended by the manufacturer may cause fire, electric shock or injury to persons.
22. Always plug heaters directly into a wall outlet/receptacle. Never use with an extension cord or reloadable power tap (outlet/power strip).
23. See Figure 1 for the follow directions.
    This heater is for use on 120 volts. The cord has a plug as shown in figure 1.See Figure 1 for grounding instruction. An adapter as shown at C is available for connecting three-blade grounding type plugs to two-slot receptacles. The green grounding plug extending from the adapter must be connected to a permanent ground such as a properly grounded outlet box. The adapter should not be used if a three-slot grounded receptacle is available.

FIGURE 1



SAVE THESE INSTRUCTIONS

PARTS LIST

Part Name	FP-30-1	FP-26-1	FP-26-2	FP-23-1	FP-18-1
Ember Bed / Logs	√	√	√	√	√
Heater	√	√	√	√	√
Blower	√	√	√	√	√
Down Light	√	√			
Main PCB	√	√	√	√	√
Control Panel PCB	√	√	√	√	√
Flame Generator Drive Motor	√	√	√	√	√
Flame Light PCB	√	√	√	√	√
Logs Light PCB	√	√	√	√	√
Ember Bed Light PCB	√	√	√	√	√
Remote Control-4 Buttons	√	√	√	√	√



Cold climate installation recommendation: When installing this unit against a Non-insulated exterior wall or chase, it is Mandatory that outer walls be insulated to Conform to applicable insulation codes.

ELECTRICAL SPECIFICATIONS

Voltage: 120 VAC, 60 Hz

Watts: 1400 Watts

ELECTRICAL CONNECTION

The unit comes standard with 6 feet (1.8m) three wire cord, exiting from the rear of the fireplace. Plan the installation to avoid the use of an extension cord. If an extension cord must be used, it must be a minimum 16 AWG; three wires with grounding type plug connection and rated not less than 1875 Watts. The cord shall not be more than 20 feet (6m) in length.

CLEANING TRIM

Clean the metal trim using a soft cloth, slightly dampened with citrus oil based product and buff With a clean soft cloth. **DO NOT** use brass polish or household cleaners as these products will damage the metal trim. Citrus oil based products can be obtained at supermarkets or hardware stores.

MAINTENANCE

The motors used on the fan and the flame generator assembly are pre-lubricated for extended bearing life and require no further lubrication. However, periodic cleaning/vacuuming of the fan/heater unit is recommended. Make sure the unit is turn OFF and unplugged whenever you are cleaning the heater or fireplace.

⚠ WARNING Make sure the power is turned off before proceeding. Any electrical repairs or rewiring of this unit should be carried out by a licensed electrician in accordance with national and local codes. If repairing or replacing any electrical component or wiring, the original wire routing, color coding and securing locations must be followed.

⚠ WARNING Electric outlet wiring must comply with local building codes and other applicable regulations to reduce the risk of fire, electrical shock and injury to persons.

⚠ WARNING Do not use this fireplace if any part of it has been under water. Immediately call a qualified service technician to inspect the fireplace and replace any part of the electrical system.

⚠ WARNING Disconnect power before attempting any maintenance or cleaning to reduce the risk of fire, electrical shock or personal injury.

⚠ WARNING During any service of this appliance, the power to the unit must be turned off. First turn the main power switch to the "OFF" position. Then remove the electrical plugfrom the wall outlet.

OPERATING INSTRUCTIONS·CONTROL FUNCTION

CONTROL PANEL ACCESS

Control panel can be accessed at upper-right corner of appliance

OPERATION INSTRUCTIONS WITHOUT REMOTE



POWER

The POWER button turns the appliance on or off. It has a memory function; the button turns off all functions at once but retains the settings in the memory. By pressing the button again, the unit will turn on at the same settings. If the TIMER has been set & time has expired all functions will stop. Press the POWER button start the appliance.

FLAME

The FLAME control switch manages the flame brightness. There are 4 brightness levels and an off position. Each time the FLAME button is pressed, the intensity of the flame decreases. When adjusting the FLAME button, a number indicating the brightness of flame will be visible on the digital display. After turning on digital display, if nothing happens within 10 seconds, digital display will turn off. There is a down light over the ember bed. When the FLAME button is in the ON position, down light will turn on, it will turn off in OFF position.

The FLAME button has locking function. Press the FLAME button for 5 seconds. The down light will turn off. When the ember bed light flashes 6 times, it is confirming the flame function is locked. To remove locking function press FLAME button for 5 seconds, the ember bed light will flash 6 times, both the flame light and ember bed will be on.

HEATER

The HEATER button turns the heater on and off. When in ON position, press the HEATER button 5 seconds and enter temperature adjustment mode. In the adjustment mode, the digital indicator will flash at .05 second intervals. There are 23 temperature settings: 72℉—73℉—74℉…82℉—ON—62℉—63℉—64℉…71℉(22℃—23℃—24℃…27℃-ON—17℃—18℃…21℃). After the temperature is selected the digital indicator will flash 5 times and will exit from setting status. After turning on the digital temperature display, if nothing happens within 10 seconds, digital display will expire.

Temperature Switch Function: With the HEATER in the ON position, press the POWER button for 5 seconds, current temperature indicator will flash 3 times; after that it will switch to another temperature.

This button has a locking function. Press the HEATER button for 10 seconds, the ember bed light will flash 6 times, indicating that the HEATER function is locked. To remove locking the function press the HEATER button 10 seconds the ember bed light will flash 6 times, indicating the locking function has been removed. Press HEATER button again, and the heating function will resume.

TIMER

The TIMER has adjustable settings at 30 minute intervals. After turning on the digital display if nothing happens for 10 seconds the display will shut off. After the desired (set) time has expired the TIMER indicator light will flash 6 times and all functions will stop. All appliance settings EXCEPT the TIMER will be retained in the memory.

After entering the time setting press the power button to remove the setting function and retain in the memory.

OPERATION INSTRUCTIONS WITH REMOTE

POWER

The POWER button turns the appliance on and off.It has a memory function; the button turns off all functions at once but retains settings in the memory.

FLAME

The FLAME button manages the flame brightness. Each time the FLAME button is pressed the intensity of the flame decreases. There are four brightness levels you can cycle through including the OFF setting. When adjusting the FLAME button a number will appear on the digital display indicating the brightness of the flame. The FLAME button does not have a locking or unlocking function.

HEATER

The HEATER button turns the heater on and off. When pressing HEATER button on the remote, the default setting temperature is 72°F(22°C).The HEATER button does not have locking or remove locking function.

TIMER

The timer may be adjusted at 30 minute intervals. The temperature setting will be visible on the digital display.

NOTE: This equipment has been tested and found to comply with the limits for Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and the receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

CAUTION This remote control uses 1 CR2032 lithium button cell battery (included). Never dispose of batteries in fire, except under conditions of controlled incineration. Failure to observe this precaution may result in an explosion.



This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

1) This device may not cause harmful interference.
2) This device must accept any interference received, including interference that may cause undesired operation.

Modifications not approved by the party responsible for compliance could void user's authority to operate the equipment.

This Class B digital apparatus complies with Canadian ICES-003.

TROUBLE SHOOTING GUIDE

MODELS: FP-30-1 / FP-26-1 / FP-26-2 FP-23-1 / FP-18-1

PROBLEM	SOLUTION
1. No power or function.	1a.Check that unit is plugged into a standard 120V wall outlet. 1b.Press power button on the control panel.
2. Main power switch lights up, but no flame effect.	2a. Open the top and back panel to check if the flame spindle has fallen off from spindle motor.
3. Have flame effect, but heater does not blow warm air.	3a. Confirm temperature setting exceeds room temperature. 3b. Try to turn on/off HEATER button several times to make sure it is in the "ON" position.
4. Heater does not work, but Power and Heater switches are in the "ON" position and thermostat is set on "HI".	4a. Turn all switches to the "OFF" position and unplug the unit from the wall outlet for 5 minutes. After 5 minutes plug the unit back into wall outlet, and operate as normal.

1 YEAR LIMITED WARRANTY

Electric Fireplaces

BASIC WARRANTY

Whalen Electric Fireplace is free from manufacturing and material defects for a period of one year from date of purchase, subject to the following conditions and limitations

1. This electric fireplace must be installed and operated at all times in accordance with the installation and operating instructions furnished with the product. Any unauthorized repair, alteration, willful abuse, accident, or misuse of the product shall nullify this warranty.
2. This warranty is non-transferable, and is made to the original owner, provided that the purchase was made through an authorized supplier of the company.
3. The warranty is limited to the repair or replacement of part(s) found to be defective in material or workmanship, provided that such part(s) have been subjected to normal conditions of use and service, after said defect is confirmed by the Company's inspection.
4. The Company may, at its discretion, fully discharge all obligations with respect to this warranty by refunding the wholesale price of the defective part(s).
5. Any installation, labor, construction, transportation, or other related costs/expenses arising from defective part(s), repair, replacement, or otherwise of same, will not be covered by this warranty, nor shall the Company assume responsibility for same.
6. The owner/user assumes all other risks, if any, including the risk of any direct, indirect or consequential loss or damage arising out of the use, or inability to use the product, except as provided by law.
7. All other warranties - expressed of implied – with respect to the product, its components and accessories, or any obligations/liabilities on the part of the Company are hereby expressly excluded.
8. The Company neither assumes, nor authorizes any third party to assume, on its behalf, any other liabilities with respect to the sale of the Whalen product.
9. The warranties as outlined within this document do not apply to non Whalen accessories used in conjunction with the installation of this product. This warranty is void if:

a. The fireplace is subjected to prolonged periods of dampness or condensation.
b. Any unauthorized alteration, willful abuse, accident, or misuse of the product.
c. You do not have the original receipt of purchase.

IF WARRANTY SERVICE IS NEEDED

Contact the company, at parts@whalenfurniture.com Or call 1-866-942-5362. Make sure you have your warranty, your sales receipt, location of purchase and the model/serial number of your Whalen products.

For update and revisions to this manual
Please see our website
www.whalenfurniture.com

Whalen Furniture Mfg ., Inc
Made in China
Printed in China

CHIMENEA ELÉCTRICA

CHIMENEA SIN RESPIRADERO CON CALENTADOR

MANUAL DE OPERACIÓN DEL PROPIETARIO

MODELOS: FP-30-1 / FP- 26-1 / FP-26-2
FP-23-1 / FP-18-1

NFORMACIÓN DE SEGURIDAD PARA EL CONSUMIDOR

LEA ESTE MANUAL ANTES DE INSTALAR Y OPERAR ESTE APARATO

⚠ ADVERTENCIA

EN CASO DE NO SEGUIR LA INFORMACIÓN EN ESTE MANUAL, UNA DESCARGA ELÉCTRICA O UN INCENDIO PUEDE PROVOCAR DAÑOS A LA PROPIEDAD, LESIONES PERSONALES O LA PÉRDIDA DE LA VIDA.

Gracias y felicitaciones por la adquisición de una chimenea Whalen. Lea las Instrucciones de Instalación antes de utilizar este aparato.

IMPORTANTE: Antes de comenzar la instalación, lea detenidamente todas las instrucciones y advertencias. El incumplimiento de estas instrucciones podría provocar una posible descarga eléctrica, riesgo de incendio, y/o lesiones y anulará la garantía.

Para el servicio a la clientela :

1-866-942-5362
Hora Estandar del Pacífico:8:30 am – 4:30 pm de Lunes a Viernes
O visite nuestra página de Internet 24 horas al dia, 7 días de la semana para ayuda en su producto
En: **www.whalenfurniture.com**
O mande un correo eléctronico a **parts@whalenfurniture.com**

Whalen Furniture Mfg ., Inc
Hecho en China
Impreso en China

MANUAL DE INSTRUCCIONES

Al utilizar aparatos eléctricos, siempre deberán tomarse precauciones básicas para disminuir el riesgo de incendio, descarga eléctrica y/o lesiones, incluyendo lo siguiente:

1. Lea todas las instrucciones antes de usar este aparato
2. Este aparato se calienta cuando está en uso. Para evitar quemaduras, no permita que la piel sin protección toque superficies calientes. Si existen, utilice las asas al mover este aparato.
   ⚠ PELIGRO Bajo determinadas condiciones anormales, se pueden generar altas temperaturas. No cubra ni obstruya parcial ni completamente el frente del calentador.
   ⚠ ADVERTENCIA Para evitar sobrecalentamiento, no cubra el calentador. El mismo no puede utilizarse en un closet.
3. ⚠ PRECAUCIÓN El aparato no debe ser utilizado por niños ni por personas con capacidades físicas, sensoriales o mentales reducidas.
4. Se deben avisar a los niños que no jueguen con el calentador.
5. Desconecte siempre este aparato cuando no esté en uso.
6. No utilice ningún calentador con cables o enchufes dañados ni después de que el aparato haya tenido un mal funcionamiento, se haya caído o dañado de cualquier manera.
7. Si el cable de alimentación de corriente está dañado, debe ser reemplazado por el fabricante, su agente de servicio u otra persona con las mismas calificaciones para prevenir los accidentes.
8. Todas las reparaciones a esta chimenea deberán ser realizadas por una persona calificada de mantenimiento.
9. Bajo ninguna circunstancia deberá modificarse esta chimenea. Las piezas que se tengan que retirar para la reparación se deben reemplazar antes de poner a funcionar esta chimenea de nuevo.
10. No lo use en exteriores.
11. Este calentador no está diseñado para usarse en baños, áreas de lavado ni en lugares interiores similares. Nunca coloque este electrodoméstico en lugares donde se pueda caer dentro de una bañera u otro recipiente con agua.
12. No coloque el cable debajo de una alfombra. No cubra el cable con tapetes, alfombras de pasillo o cubiertas similares. Coloque el cable lejos de las zonas de tránsito, donde nadie se pueda tropezar y caer.
13. Para desconectar este aparato, coloque los controles en la posición de apagado, y luego retire el enchufe del tomacorriente.
14. Solamente conecte el aparato a tomacorrientes que estén debidamente conectados a tierra.
15. Al instalar este aparato, deberá tener una conexión eléctrica a tierra de acuerdo con los códigos locales o, en ausencia de códigos locales, con el Código de Electricidad Canadiense vigente norma CSA C22.1 o para las instalaciones en EE.UU., siga los códigos locales y el Código Nacional de Electricidad, ANSI/NFPA NO.70.
16. **El calentador tiene un termostato limitador en su interior. Cuando la temperatura interna sube demasiado o se produce un calentamiento anormal, el dispositivo de protección del termostato corta el suministro de energía para evitar que la chimenea se dañe o se produzca riesgo de incendio.**
17. Los calentadores no pueden colocarse inmediatamente debajo de un tomacorriente.
18. No inserte ni permita que entren objetos extraños a las aperturas de ventilación o de extracción, ya que esto puede ocasionar una descarga eléctrica, un incendio o puede dañar el calentador.
19. A fin de evitar un posible incendio, no bloquee las entradas ni las salidas de aire de manera alguna. No lo coloque sobre superficies suaves, como una cama, donde podrían bloquearse las aberturas.
20. Este aparato tiene piezas calientes y piezas que producen arcos eléctricos o chispas en su interior. No lo utilice en áreas donde se use o guarde gasolina, pintura u otros líquidos inflamables. Esta chimenea no debe utilizarse como un soporte para secar ropa. No deben colgarse medias para los regalos de Navidad ni elementos decorativos cerca del aparato.
21. Utilice este aparato únicamente como se describe en el manual. Cualquier otro uso no recomendado por el fabricante puede ocasionar incendio, descarga eléctrica o lesiones a personas.
22. Siempre enchufe los calentadores directamente en un receptáculo o tomacorriente de pared. Nunca lo use con una extensión o un contacto múltiple con tomas reubicables (tomacorriente/enchufe múltiple).
23. Vea la Figura 1 para consultar las indicaciones a seguir. Este calentador debe utilizarse con 120 voltios. El cable incluye un enchufe tal como se muestra en la Figura 1. Vea las instrucciones de conexión a tierra en la Figura 1. Hay un adaptador, como se ilustra en C, disponible para conectar enchufes de conexión a tierra de tres clavijas en receptáculos de dos ranuras. El enchufe verde de conexión a tierra que se extiende desde el adaptador debe conectarse a una toma de tierra permanente, como la de una caja de tomacorriente correctamente conectada a tierra. No es necesario utilizar el adaptador si hay un receptáculo de tres ranuras conectado a tierra.

FIGURA 1

GUARDE ESTAS INSTRUCCIONES

LISTA DE PIEZAS

Nombre de la Pieza	FP-30-1	FP-26-1	FP-26-2	FP-23-1	FP-18-1
Lecho de brasas / Los registros	√	√	√	√	√
Conjunto de calentador	√	√	√	√	√
Ventilador	√	√	√	√	√
Abajo se enciende	√	√			
PCB (Conjunto de placa de circuito impreso) principal	√	√	√	√	√
PCB del panel de control	√	√	√	√	√
Motor de accionamiento del generador de llama	√	√	√	√	√
PCB ligero de la llama	√	√	√	√	√
PCB ligero de los registros	√	√	√	√	√
PCB ligero de lecho de brasas	√	√	√	√	√
Mando a distancia-4 botones	√	√	√	√	√

Recomendación para la instalación en climas fríos:
Al instalar esta unidad contra un compartimiento o un pared exterior sin aislamiento, es obligatorio aislar las paredes externas conforme con los códigos de aislamiento correspondientes

ESPECIFICACIONES ELÉCTRICAS
Voltaje: 120 VAC, 60 Hz
Vatios: 1400 Vatios

CONEXIÓN ELÉCTRICA

La unidad viene estándar con un cable trifilar de 6 pies (1,8 m) que sale de la parte trasera de la chimenea Planifique la instalación para evitar el uso de un cable de extensión. Si fuera necesario usar un cable de extensión, éste deberá ser como mínimo No. 16 AWG; trifilar con conector de enchufe de conexión a tierra y clasificación no inferior a 1875 vatios. El cable no deberá tener más de 20 pies (6 m) de longitud.

LIMPIEZA DE LA MOLDURA

Limpie la moldura metálica con un paño suave, ligeramente humedecido con un producto a base de aceite cítrico y púlalo con un paño suave y limpio. NO utilice productos de limpieza domésticos ni limpiametales, ya que estos productos dañarán la moldura metálica. Los productos a base de aceite cítrico pueden conseguirse en supermercados o ferreterías.

MANTENIMIENTO

Los motores que se utilizan en el ventilador y el conjunto generador de llama están prelubricados para prolongar la vida útil de los cojinetes y no es necesario lubricarlos más. Sin embargo, se recomienda limpiar/aspirar la unidad del ventilador/calentador. Asegúrese de que la unidad está **APAGADA** y **desenchufada** cuando esté limpiando el calentador o la chimenea

⚠ ADVERTENCIA Asegúrese de que la alimentación eléctrica esté desconectada antes de continuar. Toda reparación o renovación del sistema eléctrico de esta unidad deberá ser realizada por un electricista autorizado de acuerdo con códigos nacionales y locales. En caso de reparar o cambiar cualquier componente eléctrico, deberá seguirse la ruta de cables, el código de colores y los lugares de sujeción originales

⚠ ADVERTENCIA El cableado del tomacorriente eléctrico tiene que cumplir con los códigos de construcción locales y otras normas aplicables, a fin de reducir el riesgo de incendio, descarga eléctrica y lesiones a personas.

⚠ ADVERTENCIA No utilice esta chimenea si alguna de sus piezas ha estado sumergida en agua. Llame inmediatamente a un técnic de mantenimiento calificado para que inspeccione la chimenea y cambie cualquier pieza del sistema eléctrico.

⚠ ADVERTENCIA Desconecte la alimentación eléctrica antes de intentar realizar mantenimiento o limpieza para reducir el riesgo de incendio, descarga eléctrica o lesiones personales.

⚠ ADVERTENCIA Durante el mantenimiento de este aparato, deberá desconectarse la corriente a la unidad. Primero, coloque el interruptor de alimentación principal en la posición "APAGADO" ("OFF"). Luego, retire el enchufe eléctrico del tomacorriente de pared.

INSTRUCCIONES DE OPERACIÓN · FUNCIONES DE LOS

ACCESO AL PANEL DE CONTROL

Se puede tener acceso al panel de control por la esquina superior derecha del aparato.

INSTRUCCIONES DE OPERATION SIN CONTROL REMOTO



ENERGÍA

El botón de ENERGÍA enciende y apaga el aparato. El equipo tiene una función de memoria; el botón apaga todas las funciones a la vez, pero retiene los ajustes en la memoria. Al presionar el botón otra vez, la unidad se encenderá nuevamente con los mismos ajustes. Si se ha ajustado el TEMPORIZADOR y el tiempo se ha vencido, todas las funciones se detendrán. Presione el botón de ENERGÍA para encender el aparato.

LLAMA

El interruptor de control de la LLAMA controla la brillantez de la llama.Hay 4 niveles de brillantez y una posición de apagado. Cada vez que se presiona el botón LLAMA, la intensidad de la llama disminuye. Al ajustar el botón LLAMA, aparecerá en la pantalla digital un número indicando el grado de brillantez de la llama.Después de encender la pantalla digital,si no sucede nada en 10 segundos, se apagará la pantalla digital. Hay una luz hacia abajo que ilumina el lecho de brasas.Cuando el botón LLAMA se coloca en la posición ENCENDIDO,se encenderá la luz de emisión hacia abajo,y se apagará en la posición APAGADO.
El botón de la LLAMA también tiene una función de bloqueo. Presione el botón LLAMA durante 5 segundos. La luz de emisión hacia abajo se apagará. Cuando la luz del lecho de brasas destelle 6 veces, está confirmando que la función de llama está bloqueada.
Para quitar la función de bloqueo, presione el botón LLAMA durante 5 segundos, la luz del lecho de brasas destellará 6 veces, indicándole que la luz de llama y del lecho de brasas se encenderán

CALENTADOR

El botón del CALENTADOR enciende y apaga el calentador. Cuando está en la posición ENCENDIDO, presione el botón del CALENTADOR 5 segundos y seleccione la modalidad de ajuste de temperatura. En la modalidad de ajuste,el indicador digital destellará a intervalos de 0.05 segundos.Hay 23 ajustes temperatura: 72℉—73℉—74℉…82℉—ENCENDIDO—62℉—63℉—64℉…71℉(22℃—23℃—24℃…27℃- ENCENDIDO —17℃—18℃…21℃). Una vez que haya seleccionado la temperatura, el indicador digital destellará 5 veces y saldrá de la modalidad de ajuste. Después de encender la pantalla digital de temperatura, si no sucede nada en 10 segundos, se apagará la pantalla digital.
Función de cambio de temperatura: Con el CALENTADOR colocado en la posición ENCENDIDO, presione el botón de ENERGÍA durante 5 segundos, el indicador de la temperatura actual destellará 3 veces; después de lo cual cambiará a otra temperatura.
Este botón tiene una función de bloqueo. Presione el botón CALENTADOR durante 10 segundos, la luz del lecho de brasas destellará 6 veces, indicando que la función de CALENTADOR está bloqueada. Para quitar la función de bloqueo, presione el botón CALENTADOR 10 segundos y la luz del lecho de brasas destellará 6 veces, indicándole que se ha quitado la función de bloqueo. Presione nuevamente el botón CALENTADOR, y la función de calentamiento continuará funcionando.

TIMER

IEl TEMPORIZADOR tiene ajustes que se pueden regular a intervalos de 30 minutos. Después de encender la pantalla digital, si no sucede nada en10 segundos, se apagará la pantalla digital. Después que haya terminado el tiempo deseado (ajustado), la luz indicadora del TEMPORIZADOR destellará 6 veces y todas las funciones se detendrán. Todos los ajustes del aparato EXCEPTO el TEMPORIZADOR se mantendrán en la memoria.
Después de poner el tiempo deseado, presione el botón de energía para salir de la función de ajuste y mantener el tiempo en la memoria.

INSTRUCCIONES DE OPERACIÓN CON CONTROL REMOTO

ENERGÍA

El botón de ENERGÍA enciende y apaga el aparato. El equipo tiene una función de memoria; el botón apaga todas las funciones a la vez, pero retiene los ajustes en la memoria.

FLAME

El botón de LLAMA controla la brillantez de la llama. Cada vez que se presiona el botón LLAMA, la intensidad de la llama disminuye. Hay cuatro niveles de brillantez que usted puede utilizar incluso la opción de APAGADO. Al ajustar el botón LLAMA, aparecerá en la pantalla digital un número indicando el grado de brillantez de la llama. El botón LLAMA no tiene una función de bloqueo o desbloqueo.

HEATER

El botón CALENTADOR enciende y apaga el calentador. Al presionar el botón CALENTADOR en el control remoto, la temperatura predeterminada de fábrica es 72°F (22°C). El botón CALENTADOR no tiene una función de bloqueo o desbloqueo.

TIMER

El temporizador puede ajustarse a intervalos de 30 minutos. El ajuste de temperatura aparecerá en la pantalla digital.

NOTA: Este equipo ha sido probado, determinándose que cumple con los límites establecidos para un dispositivo digital de clase B, de acuerdo con la Parte 15 de las Normas de la FCC. Estos límites han sido diseñados para brindar una protección razonable contra la interferencia dañina en una instalación residencial. **Este equipo genera, utiliza, y puede irradiar energía de radiofrecuencia y, en caso de no ser instalado y utilizado de acuerdo con las instrucciones, puede causar interferencias dañinas a la recepción de radio y televisión, lo cual se puede determinar apagando y encendiendo el equipo. Le recomendamos al usuario que intente corregir la interferencia con una o más de las siguientes medidas:**

- Reorientar o reubicar la antena receptora.
- Aumentar la distancia entre el equipo y el receptor.
- Conectar el equipo a un tomacorriente en un circuito diferente al que el receptor está conectado.
- Consultar al distribuidor o alqún técnico de radio/TV con experiencia.

⚠PRECAUCIÓN Este control remoto utiliza 1 batería CR2032 de lones de litio tipo botón (incluida). Nunca deseche las baterías en el fuego, excepto en condiciones de incineración controlada. Si no se obedece esta precaución, podría producirse una explosión



Este dispositivo cumple con lo dispuesto en la Parte 15 de las Normas de la Comisión Federal de Comunicaciones (FCC por sus siglas en inglés). Su funcionamiento se encuentra sujeto a las dos condiciones siguientes:

1) Este dispositivo no puede ocasionar interferencia dañina.
2) Este dispositivo debe aceptar cualquier interferencia recibida, incluyendo la interferencia que pueda ocasionar un funcionamiento indeseable.

Las modificaciones que no estén aprobados por la parte responsable de su aceptación podrían anular el derecho del usuario para operar el equipo.Este aparato digital de Clase B cumple con la norma canadiense ICES-003.

GUÍA DE LOCALIZACIÓN Y SOLUCIÓN DE PROBLEMAS

MODELOS: FP-30-1 / FP-26-1 / FP-26-2 FP-23-1 / FP-18-1

PROBLEMA	SOLUCIÓN
1. No hay energía o no funciona.	1a.Compruebe que la unidad esté enchufada a un tomacorriente estándar de 120V. 1b.Presione el botón de energía en el panel de control.
2. Los interruptores principales se encienden, pero no hay efecto de llama.	2a. Abra el panel superior y trasero para comprobar si el husillo de la llama se ha zafado del motor de husillo.
3. El efecto de llama funciona, pero el calentador no echa aire caliente.	3a. Asegúrese de que el ajuste de temperatura sea superior a la temperatura ambiente. 3b. Trate de encender y apagar el botón CALENTADOR varias veces para asegurarse de que esté en la posición 'ENCENDIDO".
4. El calentador no funciona, pero los interruptores Energía (Power) y Calentador (Heater) están en la posición "ENCENDIDO" ("ON") y el termostato está ajustado en "ALTA" ("HI").	4a. Coloque todos los interruptores en la posición "APAGADO" ("OFF") y desenchufe la unidad del tomacorriente de la pared durante 5 minutos. Luego de 5 minutos, enchufe nuevamente la unidad al tomacorriente de la pared, y opérela de la manera habitual.

GARANTÍA LIMITADA DE 1 AÑO

Chimeneas Eléctricas

GARANTÍA BÁSICA

La Chimenea Eléctrica Whalen está libre de defectos de fabricación y materiales, durante un período de un año a partir de la fecha de compra, sujeto a las siguientes condiciones y limitaciones.

1. Esta chimenea eléctrica tiene que instalarse y operarse en todo momento de acuerdo con las instrucciones de instalación y funcionamiento suministradas con el producto. Toda reparación, alteración, maltrato intencionado, accidente, o mala utilización del producto que no esté autorizada anulará esta garantía.
2. Esta garantía no es transferible y se otorga al propietario original, siempre y cuando la compra se haya realizado a través de un proveedor autorizado de la compañía.
3. La garantía está limitada a la reparación o el reemplazo de piezas que se hayan encontrado defectuosas en relación con la mano de obra o el material, siempre y cuando estas piezas hayan sido sometidas a condiciones normales de uso y mantenimiento, luego de que dicho defecto haya sido confirmado por la inspección de la Compañía.
4. Según su criterio, la Compañía podrá cumplir con todas las obligaciones con respecto a esta garantía al reembolsar el precio mayorista de las piezas defectuosas.
5. ATodos los costos de instalación, mano de obra, construcción, transporte u otros gastos que surjan de las piezas defectuosas, la reparación, el reemplazo, o similares no estarán cubiertos por esta garantía, ni la Compañía asumirá la responsabilidad de éstos.
6. El propietario/usuario asume todos los demás riesgos, si los hay, que incluyen el riesgo de cualquier pérdida o daño directo, indirecto o resultante que surja del uso o la incapacidad para usar el producto, a excepción de lo dispuesto por ley.
7. Por la presente se excluyen expresamente todas las otras garantías, ya sean explícitas o implícitas, con respecto al producto, sus componentes y accesorios, o cualquier obligación/responsabilidad por parte de la Compañía.
8. La Compañía no asume, ni autoriza a ningún tercero a asumir en su nombre, ninguna otra responsabilidad con respecto a la venta del producto Whalen.
9. Las garantías tal como se describen en este documento no se aplican a accesorios que no sean de Whalen que se utilicen en conjunto con la instalación de este producto. Esta garantía no tendrá validez si:
   a. La chimenea es sometida a períodos prolongados de humedad o condensación.
   b. Toda alteración, maltrato intencionado, accidente, o mala utilización del producto que no esté autorizada.
   c. Usted no tiene el recibo original de compra.

SI NECESITA EL SERVICIO DE LA

Asegúrese de tener la garantía, el recibo de venta, el lugar de la compra y el número de modelo/serie de su Chimenea Whalen.

Whalen Furniture Mfg ., Inc
Hecho en China
Impreso en China

ELECTRIC FIREPLACE

VENT FREE FIREPLACE WITH HEATER

HOMEOWNERS OPERATING MANUAL

MODEL： FP-30-1

CONSUMER SAFETY INFORMATION

PLEASE READ THIS MANUAL BEFORE

INSTALLING AND OPERATING THIS APPLIANCE

⚠ WARNING

IF THE INFORMATION IN THIS MANUAL IS NOT FOLLOWED,

AN ELECTRIC SHOCK OR FIRE MAY RESULT IN PROPERTY DAMAGE,

PERSONAL INJURY, OR LOSS OF LIFE.

Thank you and congratulations on your purchase of a Whalen fireplace. Please read the Installation Instructions before using this appliance.

IMPORTANT: Read all instructions and warnings carefully before starting installation. Failure to follow these instructions may result in a possible electric shock, fire hazard, and/or injury and will void the warranty.

For Customer Service:

00-1-866-942-5362
Pacific Standard Time:8:30 a.m.-4:30 p.m.,Monday - Friday
Or visit our web site 24 hours a day,7 days a week for product assistance at
www.whalenstyle.com
Or e-mail your request to **parts@whalenfurniture.com**

ATTENTION

Also Requires

Wood Fireplace Mantel

Whalen Furniture Mfg ., Inc
Made in China
Printed in China

INSTRUCTION MANUAL

When using electrical appliances, basic precautions should always be followed to reduce the risk or fire, electrical shock, and/or injury including the following:

1. Read all instructions before using this appliance.
2. This appliance is hot when in use. To avoid burns, do not let bare skin touch hot surfaces. If provided, use handles when moving this appliance.
   ⚠ DANGER High temperatures may be generated under certain abnormal conditions. Do not partially or fully cover or obstruct the front of the heater.
   ⚠ WARNING In order to avoid overheating, do not cover the heater. It cannot be used in a closet.
3. **⚠ CAUTION** The appliance should not be used by children or persons with reduced physical, sensory or mental capabilities.
4. Children should be advised not to play with the appliance.
5. Always unplug this appliance when not in use.
6. Do not operate any heater with a damaged cord or plug or after the appliance malfunctions, or if it has been dropped or damaged in any manner.
7. If the supply cord is damaged, it must be replaced by the manufacturer, it's service agent or similarly qualified persons in order to avoid a hazard.
8. Any repairs to this fireplace should be carried out by a qualified service person.
9. Under no circumstances should this fireplace be modified. Parts having to be removed for servicing must be replaced prior to operating this fireplace again.
10. Do not use outdoors.
11. This heater is not intended for use in bathrooms, laundry areas and similar indoor locations. Never locate this appliance where it may fall into a bathtub or other water container.
12. Do not run cord under carpeting. Do not cover cord with throw rugs, runners or the like. Arrange cord away from traffic areas and where it will not be tripped over.
13. To disconnect this appliance, turn controls to the off position, then remove plug from outlet.
14. Connect to properly grounded outlets only.
15. This appliance, when installed, must be electrically grounded in accordance with local codes or, in the absence of local codes, with the current CSA C22.1 Canadian Electrical Code or for U.S.A. Installations, follow local codes and the National Electrical Code, ANSI/NFPA NO 70.
16. **There is a protective thermostat limiter inside the heater. When the inner temperature over heats, the thermostat limiter will shut off the power supply to avoid the risk of fire damage to the appliance.**
17. The heaters must not be located immediately below a socket-outlet.
18. Do not insert or allow foreign objects to enter any ventilation or exhaust opening as this may cause an electric shock or fire, or damage the appliance.
19. To prevent a possible fire, do not block air intakes or exhaust in any manner. Do not use on soft surfaces, like a bed, where opening may become blocked.
20. This appliance has hot and arcing or sparking parts inside. Do not use where gasoline, paint, or flammable liquids are used or stored. This fireplace should not be used as a drying rack for clothing. Christmas stockings or decorations should not be hung in the area of it.
21. Use this appliance only as described in the manual. Any other use not recommended by the manufacturer may cause fire, electric shock or injury to persons.
22. Always plug heaters directly into a wall outlet/receptacle. Never use with an extension cord or reloadable power tap (outlet/power strip).
23. See Figure 1 for the follow directions
    This heater is for use on 120 volts. The cord has a plug as shown in figure 1.See Figure 1 for grounding instruction. An adapter as shown at C is available for connecting three-blade grounding type plugs to two-slot receptacles. The green grounding plug extending from the adapter must be connected to a permanent ground such as a properly grounded outlet box. The adapter should not be used if a three-slot grounded receptacle is available.

FIGURE 1



SAVE THESE INSTRUCTIONS

PARTS LIST

Part Name	FP-30-1
Ember bed	√
Heater/Blower Assembly	√
Thermostat	√
Knob for Heater Temperature control	√
Down light	√
Main PCBA	√
Control Panel Circuit Board	√
Flame Generator Drive Motor	√
Flame Generator/Spinner	√
Decorative Brick Panels	√
Remote Control-4 Buttons	√

Cold climate installation recommendation: When installing this unit against a Non-insulated exterior wall or chase, it is Mandatory that outer walls be insulated to Conform to applicable insulation codes.

ELECTRICAL SPECIFICATIONS

Voltage: 120 VAC, 60 Hz

Watts: 1400 Watts

ELECTRICAL CONNECTION

The unit comes standard with 6 feet (1.8m) three wire cord, exiting from the rear of the fireplace. Plan the installation to avoid the use of an extension cord. If an extension cord must be used, it must be a minimum 16 AWG; three wires with grounding type plug connection and rated not less than 1875 Watts. The cord shall not be more than 20 feet (6m) in length.

CLEANING TRIM

Clean the metal trim using a soft cloth, slightly dampened with citrus oil based product and buff With a clean soft cloth. **DO NOT** use brass polish or household cleaners as these products will damage the metal trim. Citrus oil based products can be obtained at supermarkets or hardware stores

MAINTENANCE

The motors used on the fan and the flame generator assembly are pre-lubricated for extended bearing life and require no further lubrication. However, periodic cleaning/vacuuming of the fan/heater unit is recommended. Make sure the unit is turn OFF and unplugged whenever you are cleaning the heater or fireplace,

⚠ WARNING Make sure the power is turned off before proceeding. Any electrical repairs or rewiring of this unit should be carried out by a licensed electrician in accordance with national and local codes If repairing or replacing any electrical component or wiring, the original wire routing, color coding and securing locations must be followed.

⚠ WARNING Electric outlet wiring must comply with local building codes and other applicable regulations to reduce the risk of fire, electrical shock and injury to persons.

⚠ WARNING Do not use this fireplace if any part of it has been under water. Immediately call a qualified service technician to inspect the fireplace and replace any part of the electrical system.

⚠ WARNING Disconnect power before attempting any maintenance or cleaning to reduce the risk of fire, electrical shock or personal injury.

⚠ WARNING During any service of this appliance, the power to the unit must be turned off. First turn the main power switch to the "OFF" position. Then remove the electrical plugfrom the wall outlet.

OPERATING INSTRUCTIONS·CONTROL FUNCTION

CONTROL PANEL ACCESS
Control panel can be accessed at upper-right corner of appliance

OPERATION INSTRUCTIONS WITHOUT REMOTE



POWER

The POWER button turns the appliance on or off. It has a memory function; the button turns off all functions at once but retains the settings in the memory. By pressing the button again, the unit will turn on at the same settings. If the TIMER has been set & time has expired all functions will stop. Press the POWER button start the appliance.

FLAME

The FLAME control switch manages the flame brightness. There are 4 brightness levels and an off position. Each time the FLAME button is pressed, the intensity of the flame decreases. When adjusting the FLAME button, a number indicating the brightness of flame will be visible on the digital display. After turning on digital display, if nothing happens within 10 seconds, digital display will turn off. There is a down light over the ember bed. When the FLAME button is in the ON position, down light will turn on, it will turn off in OFF position..
The FLAME button has locking function. Press the FLAME button for 5 seconds. The down light will turn off. When the ember bed light flashes 6 times, it is confirming the flame function is locked. To remove locking function press FLAME button for 5 seconds, the ember bed light will flash 6 times, both the flame light and ember bed will be on.

HEATER

The HEATER button turns the heater on and off. When in ON position, press the HEATER button 5 seconds and enter temperature adjustment mode. In the adjustment mode, the digital indicator will flash at .05 second intervals. There are 23 temperature settings: 72℉—73℉—74℉…82℉—ON—OFF—62℉—63℉—64℉…71℉(22℃—23℃—24℃…27℃-ON—OFF—17℃—18℃…21℃). After the temperature is selected the digital indicator will flash 5 times and will exit from setting status. After turning on the digital temperature display, if nothing happens within 10 seconds, digital display will expire.
Temperature Switch Function: With the HEATER in the ON position, press the POWER button for 5 seconds, current temperature indicator will flash 3 times; after that it will switch to another temperature.
This button has a locking function. Press the HEATER button for 10 seconds, the ember bed light will flash 6 times, indicating that the HEATER function is locked. To remove locking the function press the HEATER button 10 seconds the ember bed light will flash 6 times, indicating the locking function has been removed. Press HEATER button again, and the heating function will resume.

TIMER

The TIMER has adjustable settings at 30 minute intervals. After turning on the digital display if nothing happens for 10 seconds the display will shut off. After the desired (set) time has expired the TIMER indicator light will flash 6 times and all functions will stop. All appliance settings EXCEPT the TIMER will be retained in the memory.
After entering the time setting press the power button to remove the setting function and retain in the memory.

OPERATION INSTRUCTIONS WITH REMOTE

POWER

The POWER button turns the appliance on and off.It has a memory function; the button turns off all functions at once but retains settings in the memory.

FLAME

The FLAME button manages the flame brightness. Each time the FLAME button is pressed the intensity of the flame decreases. There are four brightness levels you can cycle through including the OFF setting. When adjusting the FLAME button a number will appear on the digital display indicating the brightness of the flame. The FLAME button does not have a locking or unlocking function.

HEATER

The HEATER button turns the heater on and off. When pressing HEATER button on the remote, the default setting temperature is 72° F(22° C).The HEATER button does not have locking or remove locking function.

TIMER

The timer may be adjusted at 30 minute intervals. The temperature setting will be visible on the digital display.

NOTE: This equipment has been tested and found to comply with the limits for Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and the receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

CAUTION This remote control uses 1 CR2032 lithium button cell battery (included). Never dispose of batteries in fire, except under conditions of controlled incineration. Failure to observe this precaution may result in an explosion.



This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

1) This device may not cause harmful interference.
2) This device must accept any interference received, including interference that may cause undesired operation.

Modifications not approved by the party responsible for compliance could void user's authority to operate the equipment.

This Class B digital apparatus complies with Canadian ICES-003.

TROUBLE SHOOTING GUIDE

MODELS: FP-30-1

PROBLEM	SOLUTION
1. No power or function.	1a.Check that unit is plugged into a standard 120V wall outlet. 1b.Press power button on the control panel.
2. Main power switch lights up, but no flame effect.	2a. Open the top and back panel to check if the flame spindle has fallen off from spindle motor.
3. Have flame effect, but heater does not blow warm air.	3a. Confirm temperature setting exceeds room temperature. 3b. Try to turn on/off HEATER button several times to make sure it is in the "ON" position.
4. Heater does not work, but Power and Heater switches are in the "ON" position and thermostat is set on "HI".	4a. Turn all switches to the "OFF" position and unplug the unit from the wall outlet for 5 minutes. After 5 minutes plug the unit back into wall outlet, and operate as normal.

1 YEAR LIMITED WARRANTY

Electric Fireplaces

BASIC WARRANTY

Whalen Electric Fireplace is free from manufacturing and material defects for a period of one year from date of purchase, subject to the following conditions and limitations

1. This electric fireplace must be installed and operated at all times in accordance with the installation and operating instructions furnished with the product. Any unauthorized repair, alteration, willful abuse, accident, or misuse of the product shall nullify this warranty.
2. This warranty is non-transferable, and is made to the original owner, provided that the purchase was made through an authorized supplier of the company.
3. The warranty is limited to the repair or replacement of part(s) found to be defective in material or workmanship, provided that such part(s) have been subjected to normal conditions of use and service, after said defect is confirmed by the Company's inspection.
4. The Company may, at its discretion, fully discharge all obligations with respect to this warranty by refunding the wholesale price of the defective part(s).
5. Any installation, labor, construction, transportation, or other related costs/expenses arising from defective part(s), repair, replacement, or otherwise of same, will not be covered by this warranty, nor shall the Company assume responsibility for same.
6. The owner/user assumes all other risks, if any, including the risk of any direct, indirect or consequential loss or damage arising out of the use, or inability to use the product, except as provided by law.
7. All other warranties - expressed of implied – with respect to the product, its components and accessories, or any obligations/liabilities on the part of the Company are hereby expressly excluded.
8. The Company neither assumes, nor authorizes any third party to assume, on its behalf, any other liabilities with respect to the sale of the Whalen product.
9. The warranties as outlined within this document do not apply to non Whalen accessories used in conjunction with the installation of this product. This warranty is void if:

a. The fireplace is subjected to prolonged periods of dampness or condensation.
b. Any unauthorized alteration, willful abuse, accident, or misuse of the product.
c. You do not have the original receipt of purchase.

IF WARRANTY SERVICE IS NEEDED

Contact the company, at parts@whalenfurniture.com Or call 00-1-866-942-5362. Make sure you have your warranty, your sales receipt, location of purchase and the model/serial number of your Whalen products.

For update and revisions to this manual
Please see our website
www.whalenstyle.com

Whalen Furniture Mfg ., Inc
Made in China
Printed in China

CHIMENEA ELÉCTRICA

CHIMENEA SIN RESPIRADERO CON CALENTADOR

MANUAL DE OPERACIÓN DEL PROPIETARIO

MODELO: FP-30-1

NFORMACIÓN DE SEGURIDAD PARA EL CONSUMIDOR

LEA ESTE MANUAL ANTES DE INSTALAR Y OPERAR ESTE APARATO

⚠ ADVERTENCIA

EN CASO DE NO SEGUIR LA INFORMACIÓN EN ESTE MANUAL, UNA DESCARGA ELÉCTRICA O UN INCENDIO PUEDE PROVOCAR DAÑOS A LA PROPIEDAD, LESIONES PERSONALES O LA PÉRDIDA DE LA VIDA.

Gracias y felicitaciones por la adquisición de una chimenea Whalen. Lea las Instrucciones de Instalación antes de utilizar este aparato.

IMPORTANTE: Antes de comenzar la instalación, lea detenidamente todas las instrucciones y advertencias. El incumplimiento de estas instrucciones podría provocar una posible descarga eléctrica, riesgo de incendio, y/o lesiones y anulará la garantía.

Para el servicio a la clientela :

00-1-866-942-5362
Hora Estandar del Pacífico:8:30 am – 4:30 pm de Lunes a Viernes
O visite nuestra página de Internet 24 horas al dia, 7 dias de la semana para ayuda en su producto
En: **www.whalenstyle.com**
O mande un correo eléctronico a **parts@whalenfurniture.com**

ATENCIÓN

Requiere también
de madera chimenea
Mantel

Whalen Furniture Mfg ., Inc
Hecho en China
Impreso en China

MANUAL DE INSTRUCCIONES

Al utilizar aparatos eléctricos, siempre deberán tomarse precauciones básicas para disminuir el riesgo de incendio, descarga eléctrica y/o lesiones, incluyendo lo siguiente:

1. Lea todas las instrucciones antes de usar este aparato
2. Este aparato se calienta cuando está en uso. Para evitar quemaduras, no permita que la piel sin protección toque superficies calientes. Si existen, utilice las asas al mover este aparato.
   ⚠ PELIGRO Bajo determinadas condiciones anormales, se pueden generar altas temperaturas. No cubra ni obstruya parcial ni completamente el frente del calentador.
   ⚠ ADVERTENCIA Para evitar sobrecalentamiento, no cubra el calentador. El mismo no puede utilizarse en un closet.
3. ⚠ PRECAUCIÓN El aparato no debe ser utilizado por niños ni por personas con capacidades físicas, sensoriales o mentales reducidas.
4. Se deben avisar a los niños que no jueguen con el calentador.
5. Desconecte siempre este aparato cuando no esté en uso.
6. No utilice ningún calentador con cables o enchufes dañados ni después de que el aparato haya tenido un mal funcionamiento, se haya caído o dañado de cualquier manera.
7. Si el cable de alimentación de corriente está dañado, debe ser reemplazado por el fabricante, su agente de servicio u otra persona con las mismas calificaciones para prevenir los accidentes.
8. Todas las reparaciones a esta chimenea deberán ser realizadas por una persona calificada de mantenimiento.
9. Bajo ninguna circunstancia deberá modificarse esta chimenea. Las piezas que se tengan que retirar para la reparación se deben reemplazar antes de poner a funcionar esta chimenea de nuevo.
10. No lo use en exteriores.
11. Este calentador no está diseñado para usarse en baños, áreas de lavado ni en lugares interiores similares. Nunca coloque este electrodoméstico en lugares donde se pueda caer dentro de una bañera u otro recipiente con agua.
12. No coloque el cable debajo de una alfombra. No cubra el cable con tapetes, alfombras de pasillo o cubiertas similares. Coloque el cable lejos de las zonas de tránsito, donde nadie se pueda tropezar y caer.
13. Para desconectar este aparato, coloque los controles en la posición de apagado, y luego retire el enchufe del tomacorriente.
14. Solamente conecte el aparato a tomacorrientes que estén debidamente conectados a tierra.
15. Al instalar este aparato, deberá tener una conexión eléctrica a tierra de acuerdo con los códigos locales o, en ausencia de códigos locales, con el Código de Electricidad Canadiense vigente norma CSA C22.1 o para las instalaciones en EE.UU., siga los códigos locales y el Código Nacional de Electricidad, ANSI/NFPA NO.70.
16. **El calentador tiene un termostato limitador en su interior. Cuando la temperatura interna sube demasiado o se produce un calentamiento anormal, el dispositivo de protección del termostato corta el suministro de energía para evitar que la chimenea se dañe o se produzca riesgo de incendio.**
17. Los calentadores no pueden colocarse inmediatamente debajo de un tomacorriente.
18. No inserte ni permita que entren objetos extraños a las aperturas de ventilación o de extracción, ya que esto puede ocasionar una descarga eléctrica, un incendio o puede dañar el calentador.
19. A fin de evitar un posible incendio, no bloquee las entradas ni las salidas de aire de manera alguna. No lo coloque sobre superficies suaves, como una cama, donde podrían bloquearse las aberturas.
20. Este aparato tiene piezas calientes y piezas que producen arcos eléctricos o chispas en su interior. No lo utilice en áreas donde se use o guarde gasolina, pintura u otros líquidos inflamables. Esta chimenea no debe utilizarse como un soporte para secar ropa. No deben colgarse medias para los regalos de Navidad ni elementos decorativos cerca del aparato.
21. Utilice este aparato únicamente como se describe en el manual. Cualquier otro uso no recomendado por el fabricante puede ocasionar incendio, descarga eléctrica o lesiones a personas.
22. Siempre enchufe los calentadores directamente en un receptáculo o tomacorriente de pared. Nunca lo use con una extensión o un contacto múltiple con tomas reubicables (tomacorriente/enchufe múltiple).
23. Vea la Figura 1 para consultar las indicaciones a seguir. Este calentador debe utilizarse con 120 voltios El cable incluye un enchufe tal como se muestra en la Figura 1. Vea las instrucciones de conexión a tierra en la Figura 1. Hay un adaptador, como se ilustra en C, disponible para conectar enchufes de conexión a tierra de tres clavijas en receptáculos de dos ranuras. El enchufe verde de conexión a tierra que se extiende desde el adaptador debe conectarse a una toma de tierra permanente, como la de una caja de tomacorriente correctamente conectada a tierra. No es necesario utilizar el adaptador si hay un receptáculo de tres ranuras conectado a tierra.

FIGURA 1

GUARDE ESTAS INSTRUCCIONES

LISTA DE PIEZAS	
Nombre de la Pieza	**FP-30-1**
Lecho de brasas	√
Conjunto de calentador/ventilador	√
Termostato	√
Perilla para el control de temperatura del calentador	√
abajo se enciende	√
PCBA (Conjunto de placa de circuito impreso) principal	√
Placa de circuitos del panel de control	√
Motor de accionamiento del generador de llama	√
Generador de llama/Disco giratorio	√
paneles de ladrillo decorativos	√
Mando a distancia-4 botones	√

Recomendación para la instalación en climas fríos:
Al instalar esta unidad contra un compartimiento o un pared exterior sin aislamiento, es obligatorio aislar las paredes externas conforme con los códigos de aislamiento correspondientes

ESPECIFICACIONES ELÉCTRICAS
Voltaje: 120 VAC, 60 Hz
Vatios: 1400 Vatios

CONEXIÓN ELÉCTRICA

La unidad viene estándar con un cable trifilar de 6 pies (1,8 m) que sale de la parte trasera de la chimenea. Planifique la instalación para evitar el uso de un cable de extensión. Si fuera necesario usar un cable de extensión, éste deberá ser como mínimo No. 16 AWG; trifilar con conector de enchufe de conexión a tierra y clasificación no inferior a 1875 vatios. El cable no deberá tener más de 20 pies (6 m) de longitud.

LIMPIEZA DE LA MOLDURA

Limpie la moldura metálica con un paño suave, ligeramente humedecido con un producto a base de aceite cítrico y púlalo con un paño suave y limpio. NO utilice productos de limpieza domésticos ni limpiametales, ya que estos productos dañarán la moldura metálica. Los productos a base de aceite cítrico pueden conseguirse en supermercados o ferreterías.

MANTENIMIENTO

Los motores que se utilizan en el ventilador y el conjunto generador de llama están prelubricados para prolongar la vida útil de los cojinetes y no es necesario lubricarlos más. Sin embargo, se recomienda limpiar/aspirar la unidad del ventilador/calentador. Asegúrese de que la unidad está **APAGADA** y **desenchufada** cuando esté limpiando el calentador o la chimenea

⚠ ADVERTENCIA Asegúrese de que la alimentación eléctrica esté desconectada antes de continuar. Toda reparación o renovación del sistema eléctrico de esta unidad deberá ser realizada por un electricista autorizado de acuerdo con códigos nacionales y locales. En caso de reparar o cambiar cualquier componente eléctrico, deberá seguirse la ruta de cables, el código de colores y los lugares de sujeción originales

⚠ ADVERTENCIA El cableado del tomacorriente eléctrico tiene que cumplir con los códigos de construcción locales y otras normas aplicables, a fin de reducir el riesgo de incendio, descarga eléctrica y lesiones a personas.

⚠ ADVERTENCIA No utilice esta chimenea si alguna de sus piezas ha estado sumergida en agua. Llame inmediatamente a un técnic de mantenimiento calificado para que inspeccione la chimenea y cambie cualquier pieza del sistema eléctrico.

⚠ ADVERTENCIA Desconecte la alimentación eléctrica antes de intentar realizar mantenimiento o limpieza para reducir el riesgo de incendio, descarga eléctrica o lesiones personales.

⚠ ADVERTENCIA Durante el mantenimiento de este aparato, deberá desconectarse la corriente a la unidad. Primero, coloque el interruptor de alimentación principal en la posición "APAGADO" ("OFF"). Luego, retire el enchufe eléctrico del tomacorriente de pared.

INSTRUCCIONES DE OPERACIÓN · FUNCIONES DE LOS

ACCESO AL PANEL DE CONTROL

Se puede tener acceso al panel de control por la esquina superior derecha del aparato.

INSTRUCCIONES DE OPERATION SIN CONTROL REMOTO



ENERGÍA

El botón de ENERGÍA enciende y apaga el aparato. El equipo tiene una función de memoria; el botón apaga todas las funciones a la vez, pero retiene los ajustes en la memoria. Al presionar el botón otra vez, la unidad se encenderá nuevamente con los mismos ajustes. Si se ha ajustado el TEMPORIZADOR y el tiempo se ha vencido, todas las funciones se detendrán. Presione el botón de ENERGÍA para encender el aparato.

LLAMA

El interruptor de control de la LLAMA controla la brillantez de la llama.Hay 4 niveles de brillantez y una posición de apagado. Cada vez que se presiona el botón LLAMA, la intensidad de la llama disminuye. Al ajustar el botón LLAMA, aparecerá en la pantalla digital un número indicando el grado de brillantez de la llama.Después de encender la pantalla digital,si no sucede nada en 10 segundos, se apagará la pantalla digital. Hay una luz hacia abajo que ilumina el lecho de brasas.Cuando el botón LLAMA se coloca en la posición ENCENDIDO,se encenderá la luz de emisión hacia abajo,y se apagará en la posición APAGADO.
El botón de la LLAMA también tiene una función de bloqueo. Presione el botón LLAMA durante 5 segundos. La luz de emisión hacia abajo se apagará. Cuando la luz del lecho de brasas destelle 6 veces, está confirmando que la función de llama está bloqueada.
Para quitar la función de bloqueo, presione el botón LLAMA durante 5 segundos, la luz del lecho de brasas destellará 6 veces, indicándole que la luz de llama y del lecho de brasas se encenderán

CALENTADOR

El botón del CALENTADOR enciende y apaga el calentador. Cuando está en la posición ENCENDIDO, presione el botón del CALENTADOR 5 segundos y seleccione la modalidad de ajuste de temperatura. En la modalidad de ajuste,el indicador digital destellará a intervalos de 0.05 segundos.Hay 23 ajustes temperatura: 72℉－73℉－74℉…82℉—ENCENDIDO—APAGADO—62℉－63℉－64℉…71℉(22℃－23℃－24℃…27℃- ENCENDIDO—APAGADO—17℃－18℃…21℃). Una vez que haya seleccionado la temperatura, el indicador digital destellará 5 veces y saldrá de la modalidad de ajuste. Después de encender la pantalla digital de temperatura, si no sucede nada en 10 segundos, se apagará la pantalla digital.
Función de cambio de temperatura: Con el CALENTADOR colocado en la posición ENCENDIDO, presione el botón de ENERGÍA durante 5 segundos, el indicador de la temperatura actual destellará 3 veces; después de lo cual cambiará a otra temperatura.
Este botón tiene una función de bloqueo. Presione el botón CALENTADOR durante 10 segundos, la luz del lecho de brasas destellará 6 veces, indicando que la función de CALENTADOR está bloqueada. Para quitar la función de bloqueo, presione el botón CALENTADOR 10 segundos y la luz del lecho de brasas destellará 6 veces, indicándole que se ha quitado la función de bloqueo. Presione nuevamente el botón CALENTADOR, y la función de calentamiento continuará funcionando.

TIMER

IEl TEMPORIZADOR tiene ajustes que se pueden regular a intervalos de 30 minutos. Después de encender la pantalla digital, si no sucede nada en10 segundos, se apagará la pantalla digital. Después que haya terminado el tiempo deseado (ajustado), la luz indicadora del TEMPORIZADOR destellará 6 veces y todas las funciones se detendrán. Todos los ajustes del aparato EXCEPTO el TEMPORIZADOR se mantendrán en la memoria.
Después de poner el tiempo deseado, presione el botón de energía para salir de la función de ajuste y mantener el tiempo en la memoria.

INSTRUCCIONES DE OPERACIÓN CON CONTROL REMOTO

ENERGÍA

El botón de ENERGÍA enciende y apaga el aparato. El equipo tiene una función de memoria; el botón apaga todas las funciones a la vez, pero retiene los ajustes en la memoria.

FLAME

El botón de LLAMA controla la brillantez de la llama. Cada vez que se presiona el botón LLAMA, la intensidad de la llama disminuye. Hay cuatro niveles de brillantez que usted puede utilizar incluso la opción de APAGADO. Al ajustar el botón LLAMA, aparecerá en la pantalla digital un número indicando el grado de brillantez de la llama. El botón LLAMA no tiene una función de bloqueo o desbloqueo.

HEATER

El botón CALENTADOR enciende y apaga el calentador. Al presionar el botón CALENTADOR en el control remoto, la temperatura predeterminada de fábrica es 72°F (22°C). El botón CALENTADOR no tiene una función de bloqueo o desbloqueo.

TIMER

El temporizador puede ajustarse a intervalos de 30 minutos. El ajuste de temperatura aparecerá en la pantalla digital.

NOTA: Este equipo ha sido probado, determinándose que cumple con los límites establecidos para un dispositivo digital de clase B, de acuerdo con la Parte 15 de las Normas de la FCC. Estos límites han sido diseñados para brindar una protección razonable contra la interferencia dañina en una instalación residencial. **Este equipo genera, utiliza, y puede irradiar energía de radiofrecuencia y, en caso de no ser instalado y utilizado de acuerdo con las instrucciones, puede causar interferencias dañinas a la recepción de radio y televisión, lo cual se puede determinar apagando y encendiendo el equipo. Le recomendamos al usuario que intente corregir la interferencia con una o más de las siguientes medidas:**

- Reorientar o reubicar la antena receptora.
- Aumentar la distancia entre el equipo y el receptor.
- Conectar el equipo a un tomacorriente en un circuito diferente al que el receptor está conectado.
- Consultar al distribuidor o algún técnico de radio/TV con experiencia.

⚠PRECAUCIÓN **Este control remoto utiliza 1 batería CR2032 de Iones de litio tipo botón (incluida). Nunca deseche las baterías en el fuego, excepto en condiciones de incineración controlada. Si no se obedece esta precaución, podría producirse una explosión**



Este dispositivo cumple con lo dispuesto en la Parte 15 de las Normas de la Comisión Federal de Comunicaciones (FCC por sus siglas en inglés). Su funcionamiento se encuentra sujeto a las dos condiciones siguientes:

1) Este dispositivo no puede ocasionar interferencia dañina.
2) Este dispositivo debe aceptar cualquier interferencia recibida, incluyendo la interferencia que pueda ocasionar un funcionamiento indeseable.

Las modificaciones que no estén aprobados por la parte responsable de su aceptación podrían anular el derecho del usuario para operar el equipo.Este aparato digital de Clase B cumple con la norma canadiense ICES-003.

GUÍA DE LOCALIZACIÓN Y SOLUCIÓN DE PROBLEMAS

MODELOS: FP-30-1

PROBLEMA	SOLUCIÓN
1. No hay energía o no funciona.	1a.Compruebe que la unidad esté enchufada a un tomacorriente estándar de 120V. 1b.Presione el botón de energía en el panel de control.
2. Los interruptores principales se encienden, pero no hay efecto de llama.	2a. Abra el panel superior y trasero para comprobar si el husillo de la llama se ha zafado del motor de husillo.
3. El efecto de llama funciona, pero el calentador no echa aire caliente.	3a. Asegúrese de que el ajuste de temperatura sea superior a la temperatura ambiente. 3b. Trate de encender y apagar el botón CALENTADOR varias veces para asegurarse de que esté en la posición 'ENCENDIDO".
4. El calentador no funciona, pero los interruptores Energía (Power) y Calentador (Heater) están en la posición "ENCENDIDO" ("ON") y el termostato está ajustado en "ALTA" ("HI").	4a. Coloque todos los interruptores en la posición "APAGADO" ("OFF") y desenchufe la unidad del tomacorriente de la pared durante 5 minutos. Luego de 5 minutos, enchufe nuevamente la unidad al tomacorriente de la pared, y opérela de la manera habitual.

GARANTÍA LIMITADA DE 1 AÑO

Chimeneas Eléctricas

GARANTÍA BÁSICA

La Chimenea Eléctrica Whalen está libre de defectos de fabricación y materiales, durante un período de un año a partir de la fecha de compra, sujeto a las siguientes condiciones y limitaciones.

1. Esta chimenea eléctrica tiene que instalarse y operarse en todo momento de acuerdo con las instrucciones de instalación y funcionamiento suministradas con el producto. Toda reparación, alteración, maltrato intencionado, accidente, o mala utilización del producto que no esté autorizada anulará esta garantía.
2. Esta garantía no es transferible y se otorga al propietario original, siempre y cuando la compra se haya realizado a través de un proveedor autorizado de la compañía.
3. La garantía está limitada a la reparación o el reemplazo de piezas que se hayan encontrado defectuosas en relación con la mano de obra o el material, siempre y cuando estas piezas hayan sido sometidas a condiciones normales de uso y mantenimiento, luego de que dicho defecto haya sido confirmado por la inspección de la Compañía.
4. Según su criterio, la Compañía podrá cumplir con todas las obligaciones con respecto a esta garantía al reembolsar el precio mayorista de las piezas defectuosas.
5. ATodos los costos de instalación, mano de obra, construcción, transporte u otros gastos que surjan de las piezas defectuosas, la reparación, el reemplazo, o similares no estarán cubiertos por esta garantía, ni la Compañía asumirá la responsabilidad de éstos.
6. El propietario/usuario asume todos los demás riesgos, si los hay, que incluyen el riesgo de cualquier pérdida o daño directo, indirecto o resultante que surja del uso o la incapacidad para usar el producto, a excepción de lo dispuesto por ley.
7. Por la presente se excluyen expresamente todas las otras garantías, ya sean explícitas o implícitas, con respecto al producto, sus componentes y accesorios, o cualquier obligación/responsabilidad por parte de la Compañía.
8. La Compañía no asume, ni autoriza a ningún tercero a asumir en su nombre, ninguna otra responsabilidad con respecto a la venta del producto Whalen.
9. Las garantías tal como se describen en este documento no se aplican a accesorios que no sean de Whalen que se utilicen en conjunto con la instalación de este producto. Esta garantía no tendrá validez si:
   a. La chimenea es sometida a períodos prolongados de humedad o condensación.
   b. Toda alteración, maltrato intencionado, accidente, o mala utilización del producto que no esté autorizada.
   c. Usted no tiene el recibo original de compra.

SI NECESITA EL SERVICIO DE LA

Asegúrese de tener la garantía, el recibo de venta, el lugar de la compra y el número de modelo/serie de su Chimenea Whalen.

Whalen Furnirure Mfg ., Inc
Hecho en China
Impreso en China

ATTACHMENT C

23”insert

This is the prototype sample of the 23”insert with the control panel/buttons on the right side. We will move to the left side at same location as what we did on the 30”insert, same button shape and icons.

26”insert

This is the 2011 version we shipped

This is the prototype sample of the 2012 version with NEW log.
We will move the control panel to the left side, with same button shape and icons as the 30”insert.

30”insert





This is the 30”insert we are moving forward with the control panel in the left side, button shape and Icons as above picture.
We will do the same control panel location, shape and Icons to the 23”and 26”insert.



EXHIBIT 3

[redacted]

SETTLEMENT AGREEMENT

This Settlement Agreement ("Agreement") is entered into as of April 17, 2012 ("Effective Date"), by and between TS Investment Holding Corp., a corporation organized and existing under the laws of Delaware and with a principal place of business at 550 S Dixie Highway, Suite 300, Coral Gables, Florida, 33146., Twin-Star International, Inc., a corporation organized and existing under the laws of the State of Florida and with a principal place of business at 1690 South Congress Avenue, Suite 210, Delray Beach, Florida 33445 (collectively "Twin-Star") and Whalen Furniture Manufacturing, Inc., a corporation organized and existing under the laws of California and with a principal place of business at 1578 Air Wing Road, San Diego, California 92154 ("Whalen"). Twin-Star and Whalen shall be collectively referred to as "the Parties."

WHEREAS, on December 13, 2011, Twin-Star filed an investigation with the U.S. International Trade Commission entitled *Certain Electric Fireplaces, Components Thereof, Manuals for Same, Certain Processes For Manufacturing Or Relating To Same And Certain Products Containing Same*, Inv. No. 337-TA-826 naming Shenzhen Reliap Industrial Co., Ltd. ("Reliap"), Yue Qiu Sheng, a.k.a. Jason Yue ("Yue"), and Whalen as Proposed Respondents and alleging misappropriation of certain Twin-Star trade secrets by the Proposed Respondents, infringement of Twin-Star's registered copyrights by the Proposed Respondents, breach of contract by Yue, and tortious interference with Twin-Star's contractual relations by Reliap and Whalen.

WHEREAS, on January 13, 2012, the International Trade Commission instituted an Investigation against Respondents Yue, and Whalen (collectively "Respondents"), entitled

[redacted]

Certain Electric Fireplaces, Components Thereof, Manuals for Same, Certain Processes For Manufacturing Or Relating To Same And Certain Products Containing Same, Investigation No. 337-TA-826 ("the 826 Investigation").

WHEREAS, the 826 Investigation related to the alleged importation of certain electric fireplaces by the Respondents in violation of Section 337 of the United States Code based on copyright infringement, misappropriation of trade secrets, breach of contract, and tortious interference with contract, and sought an exclusion order to prevent the Respondents from further importation.

WHEREAS, the 826 Investigation was consolidated with an earlier investigation before the U.S. International Trade Commission, entitled *Certain Electric Fireplaces, Components Thereof, Manuals for Same, Certain Processes For Manufacturing Or Relating To Same And Certain Products Containing Same*, 337-TA-791, filed on June 17, 2011, and involving similar allegations against a subset of the Respondents (consolidated as the "826/791 Investigation").

WHEREAS, Whalen has imported, sold and had manufactured electric fireplace furniture incorporating electric fireplace inserts manufactured by and purchased from Twin-Star's former employee and allegedly current shareholder Respondent Jason Yue and Yue's company Reliap, (the "Whalen-Reliap Products");

WHEREAS, the Parties agree to resolve certain disputes, including settlement of the 826/791 Investigation, in accordance with the terms of this Agreement; and

WHEREAS, in consideration of the mutual promises, mutual covenants, and mutual agreements hereinafter set forth, and for other good and valuable consideration, the receipt and sufficiency of which are hereby acknowledged, Twin-Star and Whalen agree to the specific terms, conditions, and consideration described more particularly herein as follows:















[redacted]

IN WITNESS THEREOF, the Parties have executed this Agreement, by their duly authorized officer, as of the date last written below:

Twin-Star International, Inc. and TS Investment Holding Corp.

President
[Name and Title]

4/17/12
(Date)

Whalen Furniture Manufacturing, Inc.

President
[Name and Title]

4-17-12
(Date)

ATTACHMENT "A"









[redacted]

ATTACHMENT B TO THE SETTLEMENT AGREEMENT











[redacted]

CERTIFICATE OF SERVICE

I, Jeffrey J. Catalano, certify that a copy of the foregoing was served as indicated to the parties listed below on this 11th day of May, 2012.

James R. Holbein
Secretary
U.S. International Trade Commission
500 E Street S.W., Room 112
Washington D.C. 20436

- ☐ Via Hand Delivery
- ☐ Via Overnight Federal Express Delivery
- ☐ Via First Class Mail
- ☐ Via Facsimile
- ☒ Via Electronic Filing

Honorable David P. Shaw
U.S. International Trade Commission
500 E Street S.W., Room 317
Washington, D.C. 20436
Email: pyong.yoon@usitc.gov

- ☒ Via Hand Delivery
- ☐ Via Federal Express Delivery
- ☐ Via First Class Mail
- ☐ Via Facsimile
- ☒ Via Electronic Mail

Daniel L. Girdwood
Office of Unfair Import Investigations
U.S. International Trade Commission
500 E Street, S.W.,
Washington, D.C. 20436
Email: daniel.girdwood@usitc.gov

- ☐ Via Hand Delivery
- ☐ Via Federal Express Delivery
- ☐ Via First Class Mail
- ☐ Via Facsimile
- ☒ Via Electronic Mail

Respondent Shenzhen Reliap Industrial Co. Ltd. and Yue Qui Sheng a.k.a. Jason Yue (Public Version)
Shenzhen Reliap Industrial Co.
c/o Jason Yue
No. 3 Chuangye Road
Boan District, Shenzhen
People's Republic of China
jason@reliap.com

- ☐ Via Hand Delivery
- ☒ Via Federal Express Delivery
- ☐ Via First Class Mail
- ☐ Via Facsimile
- ☒ Via Electronic Mail

Counsel for Respondent Whalen Furniture Manufacturing Inc.
Randall S. Waier
Law Office of Randall S. Waier
20241 SW Birch Street # 103
Newport Beach, CA 92660-1783
Email: admin@waier.com

- ☐ Via Hand Delivery
- ☐ Via Federal Express Delivery
- ☐ Via First Class Mail
- ☐ Via Facsimile
- ☒ Via Electronic Mail

/s/ Jeffrey J. Catalano
One of the Attorneys for Complainants